

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : COPPER ANTI-SEIZE PASTE  
 UFI : RW2Y-T83M-200N-U9JE  
 Product code : BDS000171AE  
 Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Use of the substance/mixture : Lubricants

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries UK Limited  
 Wylds Road  
 Castlefield Industrial Estate  
 TA6 4DD Bridgwater Somerset  
 United Kingdom  
 T +44 1278 727200, F +44 1278 425644  
[hse.uk@crcind.com](mailto:hse.uk@crcind.com), [www.crcind.com](http://www.crcind.com)

##### Only Representative

CRC Industries Europe B.V.  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 T +32(0)52/45.60.11, F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com), [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +44 1278 727200  
 Office hours: 9-17h CET

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Contains :

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
 H229 - Pressurised container: May burst if heated.

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects. : P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P280 - Wear protective gloves/eye protection. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
--------------------------------	---

Derogation from labelling requirements according to CLP Article 23(c); Annex I Part 1 Section 1.3.3

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (UVCB)	EC-No.: 921-024-6 REACH-no: 01-2119475514-35	10 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
propane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
isobutane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Granulated copper substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 7440-50-8 EC-No.: 231-159-6 EC Index-No.: 029-024-00-X REACH-no: 01-2119480154-42	1 – 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
zinc powder— zinc dust (stabilised)	CAS-No.: 7440-66-6 EC-No.: 231-175-3 EC Index-No.: 030-001-01-9 REACH-no: 01-2119467174-37	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Disodium sebacate	CAS-No.: 17265-14-4 EC-No.: 241-300-3 REACH-no: 01-2120762063-61	< 2,5	Eye Irrit. 2, H319
n-hexane (Constituent) Substance listed on REACH Candidate List. substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 110-54-3 EC-No.: 203-777-6 EC Index-No.: 601-037-00-0 REACH-no: 01-2119480412-44	0,1 - <1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Comments : The substances identified as "constituents" are chemical compounds that are typically present in the UVCB substance. Their presence may be relevant for hazard classification, or other health / environmental reasons (i.e. OELs)

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.  
First-aid measures after eye contact : Rinse eyes with water as a precaution. Seek medical attention if irritation develops.  
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after ingestion : Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

- Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

- Protective equipment : Wear appropriate protective equipment and clothing during clean-up.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.  
Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.  
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### National occupational exposure and biological limit values

<b>propane (74-98-6)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>isobutane (75-28-5)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL STEL	2370 mg/m <sup>3</sup> 980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>butane (106-97-8)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m <sup>3</sup> 980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>Granulated copper (7440-50-8)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Copper
IOEL TWA	0,01 mg/m <sup>3</sup> (respirable fraction)
Remark	(Year of adoption 2014)
Regulatory reference	SCOEL Recommendations
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Cuivre (en Cu) # Koper (als Cu)
OEL TWA	0,2 mg/m <sup>3</sup> (fumées) # (rook) 1 mg/m <sup>3</sup> (poussières et brouillards de) # (stof en nevel)
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>n-hexane (110-54-3)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Hexane
IOEL TWA	72 mg/m <sup>3</sup> 20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-hexane (110-54-3)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	n-Hexane # n-Hexaan
OEL TWA	72 mg/m <sup>3</sup>
	20 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

### **DNEL and PNEC**

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day
<b>Granulated copper (7440-50-8)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	273 mg/kg bodyweight/day
Acute - local effects, inhalation	1 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	137 mg/kg bodyweight/day
Long-term - local effects, inhalation	1 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	273 mg/kg bodyweight/day
Acute - local effects, inhalation	1 mg/m <sup>3</sup>
Long-term - systemic effects, oral	0,041 mg/kg bodyweight/day
Long-term - systemic effects, dermal	137 mg/kg bodyweight/day
Long-term - local effects, inhalation	1 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	7,8 µg/l
PNEC aqua (marine water)	5,2 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	87 mg/kg dwt
PNEC sediment (marine water)	676 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	65 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	230 µg/l

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-hexane (110-54-3)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	75 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	16 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	5,3 mg/kg bodyweight/day

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protection equipment

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

### Skin protection

#### Skin and body protection:

Wear suitable protective clothing. Antistatic clothing including shoes are recommended

### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Layer thickness : > 0,10 mm.

### Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

### Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: copper.
Appearance	: Propane/butane propelled liquid.
Odour	: Solvent.

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 60 – 95 °C
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -35 °C (closed cup)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: < 20,5 mm <sup>2</sup> /s at 40 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0,81 g/cm <sup>3</sup> at 20 °C
Relative density	: 0,81 at 20 °C
Relative vapour density at 20 °C	: 3
Particle characteristics	: Not applicable

## 9.2. Additional Regulatory Information

### Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

### Other safety characteristics

VOC content : 510 g/l  
Additional information : For aerosols data for the product without propellant.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity (oral)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (dermal)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (inhalation)** : Not classified (Based on available data, the classification criteria are not met)

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
LD50 oral rat	5841 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 25,2 mg/l/4h
<b>zinc powder— zinc dust (stabilised) (7440-66-6)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5,41 mg/l/4h
<b>Disodium sebacate (17265-14-4)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
<b>Granulated copper (7440-50-8)</b>	
LD50 oral rat	500 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5,11 mg/l/4h
<b>n-hexane (110-54-3)</b>	
LD50 oral rat	24 ml/kg
LD50 oral	> 16000 mg/kg bodyweight
LD50 dermal rabbit	> 3350 mg/kg
LD50 dermal	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
<b>Skin corrosion/irritation</b>	: Causes skin irritation. pH: Not applicable
<b>propane (74-98-6)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>isobutane (75-28-5)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>butane (106-97-8)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Skin corrosion/irritation	Causes skin irritation.
<b>zinc powder— zinc dust (stabilised) (7440-66-6)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>Disodium sebacate (17265-14-4)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>Granulated copper (7440-50-8)</b>	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>n-hexane (110-54-3)</b>	
Skin corrosion/irritation	Causes skin irritation.

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

**Serious eye damage/irritation** : Not classified (Based on available data, the classification criteria are not met)  
pH: Not applicable

<b>propane (74-98-6)</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>isobutane (75-28-5)</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>butane (106-97-8)</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>zinc powder— zinc dust (stabilised) (7440-66-6)</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
<b>Disodium sebacate (17265-14-4)</b>	
Serious eye damage/irritation	Causes serious eye irritation.
<b>Granulated copper (7440-50-8)</b>	
Serious eye damage/irritation	Causes serious eye irritation.
<b>n-hexane (110-54-3)</b>	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)

**Respiratory or skin sensitisation** : Not classified (Based on available data, the classification criteria are not met)  
**Germ cell mutagenicity** : Not classified (Based on available data, the classification criteria are not met)  
**Carcinogenicity** : Not classified (Based on available data, the classification criteria are not met)  
**Reproductive toxicity** : Not classified (Based on available data, the classification criteria are not met)  
**STOT-single exposure** : May cause drowsiness or dizziness.

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-hexane (110-54-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>STOT-repeated exposure</b> : Not classified (Based on available data, the classification criteria are not met)	
<b>n-hexane (110-54-3)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** : May be fatal if swallowed and enters airways.

<b>COPPER ANTI-SEIZE PASTE</b>	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s at 40 °C

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LC50 - Fish [1]	11,4 mg/l
EC50 - Crustacea [1]	3 mg/l
EC50 72h - Algae [1]	10 mg/l
LOEC (chronic)	0,32 mg/l
NOEC (chronic)	0,17 mg/l
NOEC chronic fish	2,04 mg/l
NOEC chronic crustacea	1 mg/l

#### Disodium sebacate (17265-14-4)

LC50 - Fish [1]	> 100 mg/l Danio rerio
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna

#### Granulated copper (7440-50-8)

LC50 - Fish [1]	0,193 mg/l
EC50 - Crustacea [1]	0,1 – 1 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	0,1 – 1 mg/l
NOEC chronic fish	0,188 mg/l
NOEC chronic crustacea	0,1 – 1 mg/l

#### n-hexane (110-54-3)

LC50 - Fish [1]	> 1 mg/l
EC50 - Other aquatic organisms [1]	50 mg/l

#### 12.2. Persistence and degradability

##### COPPER ANTI-SEIZE PASTE

Persistence and degradability	Not established. No data is available on the degradability of this product.
-------------------------------	---

#### 12.3. Bioaccumulative potential

##### COPPER ANTI-SEIZE PASTE

Partition coefficient n-octanol/water (Log Kow)	Not applicable
---	----------------

##### zinc powder— zinc dust (stabilised) (7440-66-6)

Partition coefficient n-octanol/water (Log Pow)	-0,47
---	-------

##### Granulated copper (7440-50-8)

Partition coefficient n-octanol/water (Log Pow)	-0,57
---	-------

##### n-hexane (110-54-3)

Partition coefficient n-octanol/water (Log Pow)	3,9
---	-----

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### COPPER ANTI-SEIZE PASTE

Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII
---------------------------	--

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

#### COPPER ANTI-SEIZE PASTE

Additional Regulatory Information	No other effects known
Global warming potential (GWP)	1.80 (Fluorinated greenhouse gases - (EC) No 2024/573)

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations  $\geq 0.1\%$  or SCL: n-hexane (EC 203-777-6, CAS 110-54-3)

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### VOC Directive (2004/42)

VOC content : 510 g/l

##### Seveso Directive (Disaster Risk Reduction)

Seveso Additional information : P3a: FLAMMABLE AEROSOLS  
'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1  
E2: Hazardous to the Aquatic Environment in Category Chronic 2

##### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
3	Composition/information on ingredients	<b>Modified</b>
3	Comments (below composition)	<b>Added</b>
8.2	Indicative Occupational Exposure Limit (IOEL)	<b>Modified</b>
8.2	DNEL and PNEC	<b>Modified</b>
15.1	Substance(s) listed on the REACH Candidate List	<b>Added</b>

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

# COPPER ANTI-SEIZE PASTE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

H411	Toxic to aquatic life with long lasting effects.
------	--

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.