

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/02/2025 Revision date: 28/08/2024 Supersedes version of: 12/06/2023 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Polymer Remover

UFI : CRMX-9873-H00Y-QYDS

Product code : BDS001937AE
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele Belgium

T +32(0)52/45.60.11, F +32(0)52/45.00.34

hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 2 H223;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Carcinogenicity, Category 2 H351
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Flammable aerosol. Suspected of causing cancer. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

GHS08

Signal word (CLP) : Warning

Contains : dichloromethane; methylene chloride; Hydrocarbons, C10, aromatics, <1% naphthalene

Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H223 - Flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

H351 - Suspected of causing cancer.

H412 - Harmful to aquatic life with long lasting effects.

: P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P201 - Obtain special instructions before use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/eye protection.
P308+P313 - IF exposed or concerned: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dichloromethane; methylene chloride substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 75-09-2 EC-No.: 200-838-9 EC Index-No.: 602-004-00-3 REACH-no: 01-2119480404-41	50 – 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
propane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	5 – 10	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	5 – 10	Flam. Gas 1, H220 Press. Gas (Liq.), H280
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (BE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Hydrocarbons, C10, aromatics, <1% naphthalene	EC-No.: 918-811-1 REACH-no: 01-2119463583- 34	5 – 10	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	1 – 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	(50 ≤ C < 100) Eye Irrit. 2; H319

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public

waters. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual

contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do

not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective

equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Avoid prolonged

exposure. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

28/08/2024 (Revision date) BE - en 4/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

propane (74-98-6)		
Belgium - Occupational Exposure Limits		
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)	
OEL TWA	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
isobutane (75-28-5)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan	
OEL STEL	2370 mg/m³	
	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
butane (106-97-8)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan	
OEL STEL	2370 mg/m³	
	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
dichloromethane; methylene chloride (75-09-2)		
EU - Indicative Occupational Exposure Lim	it (IOEL)	
Local name	Methylene chloride; Dichloromethane	
IOEL TWA	353 mg/m³	
	100 ppm	
IOEL STEL	706 mg/m³	
	200 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164	
EU - Biological Limit Value (BLV)		
Local name	Methylene chloride	
BLV	4 % Parameter: COHb - Medium: Blood0,3 mg/l Parameter: methylene chloride - Medium: urine1 mg/l Parameter: methylene chloride - Medium: blood	
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs	
Belgium - Occupational Exposure Limits		
Local name	Chlorure de méthylène (Dichlorométhane) # Methyleenchloride	
OEL TWA	177 mg/m³	
	50 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dichloromethane; methylene chloride (75-09-2)		
OEL STEL	706 mg/m³	
	200 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
ethanol; ethyl alcohol (64-17-5)		
Belgium - Occupational Exposure Limits		
Local name	Alcool éthylique # Ethanol	
OEL TWA	1907 mg/m³	
	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

DNEL and **PNEC**

NEE did I NEO		
dichloromethane; methylene chloride (75-09-2)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	12 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	176 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,06 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	44 mg/m³	
Long-term - systemic effects, dermal	5,82 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0,31 mg/l	
PNEC aqua (marine water)	0,031 mg/l	
PNEC aqua (intermittent, freshwater)	0,27 mg/l	
PNEC aqua (intermittent, marine water)	0,027 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	2,57 mg/kg dwt	
PNEC sediment (marine water)	0,26 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,33 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	26 mg/l	
ethanol; ethyl alcohol (64-17-5)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	1900 mg/m³	
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol; ethyl alcohol (64-17-5)		
Long-term - systemic effects, inhalation	950 mg/m³	
DNEL/DMEL (General population)		
Acute - local effects, inhalation	950 mg/m³	
Long-term - systemic effects,oral	87 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	114 mg/m³	
Long-term - systemic effects, dermal	206 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0,96 mg/l	
PNEC aqua (marine water)	0,79 mg/l	
PNEC aqua (intermittent, freshwater)	2,75 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3,6 mg/kg dwt	
PNEC sediment (marine water)	2,9 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,63 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	0,72 g/kg food	
PNEC (STP)		
PNEC sewage treatment plant	580 mg/l	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Vinyl polyalcohol protective gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless.

Appearance : Propane/butane propelled liquid.

Odour : Solvent.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available
Flammability : Flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

 Lower explosion limit
 : Not available

 Upper explosion limit
 : Not available

 Flash point
 : 12 °C (closed cup)

 Auto-ignition temperature
 : > 200 °C

 Decomposition temperature
 : Not available

: Not applicable pН Viscosity, kinematic : 67,8 mm²/s at 20 °C Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available : 1,18 g/cm3 at 20 °C Density : 1,18 at 20 °C Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 25-50 %

Other safety characteristics

VOC content : 1025 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)

: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal)

: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)	
dichloromethane; methylene chloride (75-09-2)		
LD50 oral rat	> 2000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat	86 mg/l/4h	
ethanol; ethyl alcohol (64-17-5)		
LD50 oral rat	15010 mg/kg bodyweight	
LD50 dermal	15800 mg/kg bodyweight	
LC50 Inhalation - Rat (Vapours)	> 116,9 mg/l/4h	
Hydrocarbons, C10, aromatics, <1% naphthalene		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	> 5000 mg/m³	
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable	

Serious eye damage/irritation : Causes serious eye irritation.

pH: Not applicable

Respiratory or skin sensitisation

: Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity

: Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

dichloromethane; methylene chloride (75-09-2)

STOT-single exposure May cause drowsiness or dizziness.

Hydrocarbons, C10, aromatics, <1% naphthalene

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

ethanol; ethyl alcohol (64-17-5)

NOAEL (subchronic, oral, animal/female, 90 days) > 9400 mg/kg bodyweight

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Polymer Remover		
Vaporizer	Aerosol	
Viscosity, kinematic	67,8 mm²/s at 20 °C	
dichloromethane; methylene chloride (75-09-2)		
Viscosity, kinematic	0,316 mm²/s	
Hydrocarbons, C10, aromatics, <1% naphthalene		
Viscosity, kinematic	1,23 mm²/s	

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

LC50 - Fish [1]

: Harmful to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term (acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Harmful to aquatic life with long lasting effects.

dichloromethane; methylene chloride (75-09-2)

EC50 96h - Algae [1]	> 662 mg/l Pseudokirchneriella subcapitata	
ethanol; ethyl alcohol (64-17-5)		
LC50 - Fish [1]	14,2 g/l	
EC50 - Other aquatic organisms [1]	5012 mg/l	
ErC50 algae	275 mg/l	
NOEC (chronic)	9,6 mg/l	
Hydrocarbons, C10, aromatics, <1% naphthalene		

193 mg/l Pimephales promelas

LC50 - Fish [1]	2 – 5 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	3 – 10 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	11 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Polymer Remover

Persistence and degradability Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (Log Kow) Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dichloromethane; methylene chloride (75-09-2)		
Partition coefficient n-octanol/water (Log Pow) 1,25		
ethanol; ethyl alcohol (64-17-5)		
Partition coefficient n-octanol/water (Log Pow)	-0,32	
Hydrocarbons, C10, aromatics, <1% naphthalene		
Partition coefficient n-octanol/water (Log Pow)	4	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Polymer Remover	
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Polymer Remover	
Other information	No other effects known
Global warming potential (GWP)	6.82 (Fluorinated greenhouse gases - (EC) No 2024/573)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper shippin	14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS	
Transport document description					
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
4.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
4.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.5. Environmental haz	zards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR):MP9Transport category (ADR):2Special provisions for carriage - Packages (ADR):V14Special provisions for carriage - Loading, unloading:CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 1025 g/l

Detergent Regulation (648/2004)

Labelling of contents	
Component	%
halogenated hydrocarbons	≥30%
aromatic hydrocarbons	5-15%

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:		
Aerosol 2	Aerosol, Category 2	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H223	Flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.