

# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name or designation	DS-90		
of the mixture			
Registration number	-		
Synonyms	None.		
Product code	BDS002602AE		
Issue date	26-May-2020		
Version number	2.0		
Revision date	07-April-2022		
Supersedes date	26-May-2020		
1.2. Relevant identified uses of t	the substance or mixture and uses advised against		
Identified uses	Cleaners - Heavy duty		
Uses advised against	None known.		
1.3. Details of the supplier of the	e safety data sheet		
Company name	CRC Industries UK Ltd.		
Address	Wylds Road		
	Castlefield Industrial Estate		
	TA6 4DD Bridgwater Somerset		
	United Kingdom		
Telephone	+44 1278 727200		
Fax	+44 1278 425644		
E-mail	hse.uk@crcind.com		
Website	www.crcind.com		
Company name	CRC Industries Europe bv		
Address	Touwslagerstraat 1		
	9240 Zele		
	Belgium		
Telephone	+32(0)52/45.60.11		
Fax	+32(0)52/45.00.34		
E-mail	hse@crcind.com		
Website	www.crcind.com		
	Tel (144)(0)4070 70 7000 (office bourse 0.47h CMT)		

1.4. Emergency telephone number

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

# Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Health hazards		
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.

Specific target organ toxicity - single exposure		Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Environmental hazards			
Hazardous to the aquatic long-term aquatic hazard	environment,	Category 3	H412 - Harmful to aquatic life with long lasting effects.
2.2. Label elements			
Label according to Regulation (E	EC) No. 1272/2008	as amended	
Contains:	Orange, sweet, e	extract, Propan-2-ol; Isopropyl alcohol; Isopr	opanol
Hazard pictograms	$\wedge$	<u>^</u>	
		•	
Signal word	Danger	•	
Hazard statements			
H222	Extremely flamm	able aerosol.	
H229	Pressurized container: May burst if heated.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious e	eye irritation.	
H336	May cause drows	siness or dizziness.	
H412	Harmful to aquat	ic life with long lasting effects.	
Precautionary statements			
Prevention			
P102	Keep out of reacl	h of children.	
P210	Keep away from	heat, hot surfaces, sparks, open flames and	other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.		
P251	Do not pierce or burn, even after use.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
Response	Not assigned.		
Storage			
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal			
P501	Dispose of conte	nts/container in accordance with local/region	nal/national/international regulations.
Supplemental label information	Regulation (EC)	No 648/2004 on detergents: perfumes: Limo	nene
2.3. Other hazards	This mixture does not contain substances assessed to be $vPvB / PBT$ according to Regulation		

# SECTION 3: Composition/information on ingredients

Mixture

#### **General information**

Chemical name	%	CAS-No. / EC No.	<b>REACH Registration No</b>	. Index No.	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol	75 - 100	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	#
Classificat	ion: Flam. Liq. 2	;H225, Eye Irrit. 2;H	319, STOT SE 3;H336		
Orange, sweet, extract	<25	8028-48-6 232-433-8	01-2119493353-35	-	
Classificat		;H226, Skin Irrit. 2;H uatic Chronic 2;H41	l315, Skin Sens. 1;H317, <i>I</i> I	Asp. Tox.	
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classificat	ion: Press. Gas;	H280			
ethanol; ethyl alcohol	1 - 5	64-17-5 200-578-6	01-2119457610-43	603-002-00-5	#

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

#### List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This substance has been assigned Union workplace exposure limit(s).

**Composition comments** 

**General information** 

The full text for all H-statements is displayed in section 16.

#### **SECTION 4: First aid measures**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

o. i. Personal precautions, protec	cive equipment and emergency procedures
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Not available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Expos Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	
ethanol; ethyl alcohol (CAS 64-17-5)	TWA	1920 mg/m3	
		1000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3	
		500 ppm	
	TWA	999 mg/m3	
		400 ppm	
logical limit values	No biological exposure limits noted for the ingredient(s).		

Follow standard monitoring procedures.

## procedures Derived no effect levels (DNELs)

**Recommended monitoring** 

# General Population

Components	Value	Assessment factor	Notes
ethanol; ethyl alcohol (CAS 64-17-5)			
Long-term, Systemic, Dermal Long-term, Systemic, Oral Short-term, Local, Inhalation	206 mg/kg bw/day 87 mg/kg bw/day 950 mg/m3	40 20	Repeated dose toxicity Repeated dose toxicity respiratory tract irritation
Orange, sweet, extract (CAS 8028-48-6)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	4.44 mg/kg bw/day 7.78 mg/m3	225 225	Repeated dose toxicity Repeated dose toxicity
Propan-2-ol; Isopropyl alcohol; Isopropano	I (CAS 67-63-0)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	319 mg/kg bw/day 89 mg/m3 26 mg/kg bw/day	2 2 2	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment factor	Notes
ethanol; ethyl alcohol (CAS 64-17-5)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	343 mg/kg bw/day 950 mg/m3	24	Repeated dose toxicity
Short-term, Local, Inhalation	1900 mg/m3		respiratory tract irritation

	0000 40 0			
Orange, sweet, extract (CAS		04.4	440 5	
Long-term, Systemic, Inh Short-term, Local, Derma		31.1 mg/m3 185.8 μg/cm²	112.5 30	Repeated dose toxicity Skin Sensitisation
Propan-2-ol; Isopropyl alcoho	ol; Isopropanol (	CAS 67-63-0)		
Long-term, Systemic, De Long-term, Systemic, Inł		888 mg/kg bw/day 500 mg/m3	1 1	
Predicted no effect concentration	ons (PNECs)			
Components		Value	Assessment	factor Notes
ethanol; ethyl alcohol (CAS 6	4-17-5)			
Freshwater Sediment (marine water) Soil	1	0.96 mg/l 2.9 mg/kg 0.63 mg/kg	10 1000	
Orange, sweet, extract (CAS	8028-48-6)	J. J. J. J.		
Freshwater Sediment (freshwater) Soil STP	,	5.4 μg/l 1.3 mg/kg 0.261 mg/kg 2.1 mg/l	50 10	
Propan-2-ol; Isopropyl alcoho	ol; Isopropanol (	CAS 67-63-0)		
Freshwater Secondary poisoning Sediment (freshwater) Soil		140.9 mg/l 160 mg/kg 552 mg/kg 28 mg/kg	1 30	Oral
8.2. Exposure controls				
Appropriate engineering controls Individual protection measures General information	<ul> <li>Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.</li> <li>res, such as personal protective equipment</li> <li>Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective</li> </ul>			
	equipment.			
Eye/face protection	Wear safety	glasses with side shields (c	or goggles). Use eye	protection conforming to EN 166.
Skin protection				
- Hand protection	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.			
- Other	Wear appropriate chemical resistant clothing.			
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
Hygiene measures	after handling clothing and	g the material and before e	ating, drinking, and/	nygiene measures, such as washing or smoking. Routinely wash work Contaminated work clothing should not
Environmental exposure controls	from ventilati requirements	on or work process equipm of environmental protection	nent should be chec on legislation. Fume	all environmental releases. Emissions ked to ensure they comply with the scrubbers, filters or engineering to reduce emissions to acceptable
SECTION 9: Physical and	chomical n	roportios		

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Colour	Colourless.
Odour	Citrus.
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	-114.1 °C (-173.4 °F) estimated

Initial boiling point and boiling range	78 °C (172.4 °F) estimated
Flash point	12.0 °C (53.6 °F) Closed cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	plosive limits
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	12 % estimated
Vapour pressure	17070.1 hPa estimated
Vapour density	Not available.
Relative density	0.8 g/cm3 at 20°C
Solubility(ies)	
Solubility (water)	Soluble in water
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
VOC	780 g/l
SECTION 10: Stability and reactivity	

•	•
10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Acids. Strong oxidising agents. Chlorine. Isocyanates.
10.6. Hazardous decomposition products	Carbon oxides.

# **SECTION 11: Toxicological information**

General information Occupational exposure to the substance or mixture may cause adverse effects.

# Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

# 11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Components	Species	Test Results
ethanol; ethyl alcohol (CAS	64-17-5)	
Acute		
Dermal		
LD50	Rabbit	> 15800 mg/kg
Inhalation		
LC50	Rat	116.8 - 133.8 mg/l, 4 h
Oral		
LD50	Rat	10470 mg/kg

Components	Species	Test Results
Orange, sweet, extract (CAS 8028	-48-6)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	5000 mg/kg bw/day
Oral		
LD50	Rat	> 2000 mg/kg/day
Propan-2-ol; Isopropyl alcohol; Iso	propanol (CAS 67-63-0)	
Acute		
Inhalation		
LC50	Rat	> 25000 mg/m3, 6 h
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	Based on available data, the classification criteria ar	e not met.
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity	Based on available data, the classification criteria ar	e not met.
Carcinogenicity	Based on available data, the classification criteria an	e not met.
Reproductive toxicity	Based on available data, the classification criteria an	e not met.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria ar	e not met.
Aspiration hazard	Based on available data, the classification criteria an	e not met.
Mixture versus substance information	Not available.	

# **SECTION 12: Ecological information**

12.1. Toxicity	Harmful to aquatic life with long lasting effects.		
Components Species Test Res		Test Results	
ethanol; ethyl alcohol (CAS 64	-17-5)		
Acute			
	EC50	Selenastrum capricornutum (new name Pseudokirchneriella subcapitata)	> 100 mg/l, 48 hours
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	12340 mg/l, 48 hours
Fish	LC50	Leuciscus idus	> 100 mg/l, 48 hours
		Oncorhynchus mykiss	13000 mg/l, 96 hours
		Oryzias latipes	12000 - 16000 mg/l, 96 hours
		Pimephales promelas	14200 mg/l, 96 hours
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 days
Propan-2-ol; Isopropyl alcohol;	Isopropanol (CAS	67-63-0)	
Aquatic			
Acute			
Crustacea	LC50	Brine shrimp (Artemia salina)	> 10000 mg/l, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
12.2. Persistence and degradability	No data is ava	ailable on the degradability of any ingredie	nts in the mixture.
12.3. Bioaccumulative poten	tial		
Partition coefficient n-octanol/water (log Kow)			
ethanol; ethyl alcohol		-0.31	
Propan-2-ol; Isopropyl alc		0.05	
Bioconcentration factor (BC	<li>F) Not available.</li>		

12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
12.6. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential. GWP: 0

# **SECTION 13: Disposal considerations**

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

### ADR

ADR		
14.	1. UN number	UN1950
14.	2. UN proper shipping	AEROSOLS, flammable
nar		
14.:	3. Transport hazard class	es)
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Hazard No. (ADR)	Not available.
	Tunnel restriction code	D
14.4	4. Packing group	Not available.
14.	5. Environmental hazards	
	6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	user	
RID		
14.	1. UN number	UN1950
14.:	2. UN proper shipping	AEROSOLS, flammable
nar		
14.:	3. Transport hazard class	es)
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	4. Packing group	Not available.
	5. Environmental hazards	
	6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	user	
ADN		
	1. UN number	UN1950
	2. UN proper shipping	AEROSOLS, flammable
nar		
14.	3. Transport hazard class	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	4. Packing group	Not available.
	5. Environmental hazards	
	6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	user	
IATA		
14.	1. UN number	UN1950

14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class	(es)
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not available.
14.5. Environmental hazards	No
ERG Code	10L
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
14.1. UN number	UN1950
14.2. UN proper shipping	Aerosols, flammable
name	
14.3. Transport hazard class	(es)
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not available.
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.
ADN; ADR; IATA; IMDG; RID	



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Retained direct EU regulations** 

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### Authorisations

### Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

#### **Restrictions on use**

## Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

ethanol; ethyl alcohol (CAS 64-17-5)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

#### **Other EU regulations**

#### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ethanol; ethyl alcohol (CAS 64-17-5)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

No Chemical Salety Assessment has been carried out.

#### **SECTION 16: Other information**

List of abbreviations

List of appreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP). CAS: Chemical Abstract Service. Ceiling: Short Term Exposure Limit Ceiling value.
	CEN: European Committee for Standardization. CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
	GWP: Global Warming Potential.
	IATA: International Air Transport Association.
	IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods.
	MAC: Maximum Allowed Concentration.
	MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
	MARPOL: International Convention for the Prevention of Pollution from Ships.
	PBT: Persistent, bioaccumulative and toxic.
	REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No
	1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. VOC: Volatile organic compounds. vPvB: Very persistent and very bioaccumulative. STEL: Short-term Exposure Limit.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any H-statements not written out in full under	
Sections 2 to 15	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H280 Contains gas under pressure; may explode if heated.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Revision information Training information Disclaimer H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.