

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/02/2025 Revision date: 02/09/2024 Supersedes version of: 02/06/2023 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Carb & EGR Cleaner
UFI : 6HCX-P8Y0-400G-66FK

Product code : BDS002713AE
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele Belgium

T +32(0)52/45.60.11, F +32(0)52/45.00.34 hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Aspiration hazard, Category 1 H304 Hazardous to the aquatic environment – Acute Hazard, H400

Category 1

Hazardous to the aquatic environment – Chronic Hazard, H410

Category 1

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :







GHS02

GHS07

GHS09

Signal word (CLP) : Danger

02/09/2024 (Revision date) BE - en 1/18

Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains : Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; butanone; ethyl methyl

ketone;propan-2-ol; isopropyl alcohol; isopropanol;cyclohexane;acetone; propan-2-one;

propanone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

11440 May dauge drowonieds or dizzmess.

H410 - Very toxic to aquatic life with long lasting effects.P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514- 35	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cyclohexane substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 110-82-7 EC-No.: 203-806-2 EC Index-No.: 601-017-00-1 REACH-no: 01-2119463273-	25 – 50	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Carbon dioxide (CO2) (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	5 – 10	Press. Gas (Comp.), H280
butanone; ethyl methyl ketone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical

attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good

industrial hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Carbon dioxide (CO2) (124-38-9)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name Carbon dioxide

02/09/2024 (Revision date) BE - en 4/18

Safety Data Sheet

Carbon dioxide (CO2) (124-38-9)		
IOEL TWA	9000 mg/m³	
	5000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Belgium - Occupational Exposure Limits		
Local name	Carbone (dioxyde de) # Koolstofdioxide	
OEL TWA	9131 mg/m³	
3,.	5000 ppm	
OEL STEL	54784 mg/m³	
	30000 ppm	
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
butanone; ethyl methyl ketone (78-93-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Butanone	
IOEL TWA	600 mg/m³	
	200 ppm	
IOEL STEL	900 mg/m³	
	300 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	2-Butanone # 2-Butanon	
OEL TWA	600 mg/m³	
	200 ppm	
OEL STEL	900 mg/m³	
	300 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Belgium - Occupational Exposure Limits		
Local name	Alcool isopropylique # Isopropylalcohol	
OEL TWA	500 mg/m³	
	200 ppm	
OEL STEL	1000 mg/m³	
	400 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cyclohexane (110-82-7)		
EU - Indicative Occupational Exposure L	imit (IOEL)	
Local name	Cyclohexane	
IOEL TWA	700 mg/m³	
	200 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Belgium - Occupational Exposure Limits		
Local name	Cyclohexane # Cyclohexaan	
OEL TWA	350 mg/m³	
	100 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
acetone; propan-2-one; propanone ((67-64-1)	
EU - Indicative Occupational Exposure L	imit (IOEL)	
Local name	Acetone	
IOEL TWA	1210 mg/m³	
	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	Acétone # Aceton	
OEL TWA	594 mg/m³	
	246 ppm	
OEL STEL	1187 mg/m³	
	492 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
DNEL/DMEL (Workers)	DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	2035 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	699 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	608 mg/m³		
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day		
butanone; ethyl methyl ketone (78-93-3)			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	600 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	31 mg/kg bodyweight/day		

Safety Data Sheet

butanone; ethyl methyl ketone (78-93-3)	
Long-term - systemic effects, inhalation	106 mg/m³
•	-
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	55,8 mg/l
PNEC aqua (marine water)	55,8 mg/l
PNEC aqua (intermittent, freshwater)	55,8 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	284,74 mg/kg dwt
PNEC sediment (marine water)	284,7 mg/kg dwt
PNEC (Soil)	
PNEC soil	22,5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	1000 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	709 mg/l
propan-2-ol; isopropyl alcohol; isopropanol	(67-63-0)
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
PNEC (Soil)	
PNEC soil	28 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	160 mg/kg food
PNEC (STP)	
	2251 mg/l

Safety Data Sheet

cyclohexane (110-82-7)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	1400 mg/m³	
Acute - local effects, inhalation	1400 mg/m³	
Long-term - systemic effects, dermal	2016 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	700 mg/m³	
Long-term - local effects, inhalation	700 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	412 mg/m³	
Acute - local effects, inhalation	412 mg/m³	
Long-term - systemic effects,oral	59,4 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	206 mg/m³	
Long-term - systemic effects, dermal	1186 mg/kg bodyweight/day	
Long-term - local effects, inhalation	206 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	44,7 µg/l	
PNEC aqua (marine water)	4,47 µg/l	
PNEC aqua (intermittent, freshwater)	9 µg/l	
PNEC aqua (intermittent, marine water)	0,9 μg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3,6 mg/kg dwt	
PNEC sediment (marine water)	0,36 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,694 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	3,24 mg/l	
acetone; propan-2-one; propanone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10,6 mg/l	
	, 3	
PNEC aqua (marine water)	1,06 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)		
PNEC (Sediment)		
PNEC sediment (freshwater)	30,4 mg/kg dwt	
PNEC sediment (marine water)	3,04 mg/kg dwt	
PNEC (Soil)		
PNEC soil	29,5 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless.

Appearance : CO2 propelled liquid.

Odour : Solvent.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : -35 °C (closed cup)

Auto-ignition temperature : > 200 °C Decomposition temperature : Not available : Not applicable рΗ : < 10 mm²/s at 20 °C Viscosity, kinematic : Insoluble in water. Solubility Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 0,76 g/cm3 at 20 °C : 0,76 at 20 °C Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

Other safety characteristics

VOC content : 715 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (dermal): Not classified (Based on available data, the classification criteria are not met)Acute toxicity (inhalation): Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

Hydrocarbons, C6-C7, n-alkanes, isoalkar	nes, cyclics, <5% n-hexane	
LD50 oral rat	5841 mg/kg	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight	
LC50 Inhalation - Rat	> 25,2 mg/l/4h	
butanone; ethyl methyl ketone (78-93-3)		
LD50 oral rat	> 2193 mg/kg bodyweight	
LD50 dermal	6400 mg/kg bodyweight	
LC50 Inhalation - Rat (Dust/Mist)	> 5000 mg/l/4h	
propan-2-ol; isopropyl alcohol; isopropan	ol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight	
cyclohexane (110-82-7)		
LD50 oral rat	> 5000 mg/kg bodyweight	
LD50 dermal rabbit	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat	> 32,88 mg/l/4h	
acetone; propan-2-one; propanone (67-64	-1)	
LD50 oral rat	5800 mg/kg bodyweight	
LD50 dermal	> 15688 mg/kg bodyweight	
LC50 Inhalation - Rat	76 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	pH: Not applicableCauses serious eye irritation.pH: Not applicable	
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)	
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity Reproductive toxicity	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) 	
STOT-single exposure	: May cause drowsiness or dizziness.	
Hydrocarbons, C6-C7, n-alkanes, isoalkar	nes, cyclics, <5% n-hexane	
STOT-single exposure	May cause drowsiness or dizziness.	
butanone; ethyl methyl ketone (78-93-3)		
STOT-single exposure	May cause drowsiness or dizziness.	
propan-2-ol; isopropyl alcohol; isopropan	ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.	
cyclohexane (110-82-7)		
STOT-single exposure	May cause drowsiness or dizziness.	
acetone; propan-2-one; propanone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Carb & EGR Cleaner		
Vaporizer	Aerosol	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carb & EGR Cleaner	
Viscosity, kinematic < 10 mm²/s at 20 °C	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Viscosity, kinematic	0,7 mm²/s at 20 °C

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

 $\label{thm:local_equation} \mbox{Hazardous to the aquatic environment, short-term}$

(acute)

: Very toxic to aquatic life.

 $\label{thm:long-term} \mbox{Hazardous to the aquatic environment, long-term}$

: Very toxic to aquatic life with long lasting effects.

(chronic)

,		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LC50 - Fish [1]	11,4 mg/l	
EC50 - Crustacea [1]	3 mg/l	
EC50 72h - Algae [1]	10 mg/l	
LOEC (chronic)	0,32 mg/l	
NOEC (chronic)	0,17 mg/l	
NOEC chronic fish	2,04 mg/l	
NOEC chronic crustacea	1 mg/l	
butanone; ethyl methyl ketone (78-93-3)		
LC50 - Fish [1]	2993 mg/l	
EC50 - Crustacea [1]	308 mg/l	
EC50 - Other aquatic organisms [1]	308 mg/l	
EC50 72h - Algae [1]	1972 mg/l	
EC50 96h - Algae [1]	2029 mg/l	
propan-2-ol; isopropyl alcohol; isopropa	anol (67-63-0)	
LC50 - Fish [1]	10000 mg/l	
LC50 - Fish [2]	9640 mg/l	
cyclohexane (110-82-7)		
LC50 - Fish [1]	4,53 mg/l	
EC50 - Crustacea [1]	0,9 mg/l Daphnia magna (Water flea)	
acetone; propan-2-one; propanone (67-64-1)		
LC50 - Fish [1]	5540 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)	
EC50 - Other aquatic organisms [1]	12600 mg/l Daphnia magna (Water flea)
LOEC (chronic)	> 79 mg/l
NOEC (chronic)	≥ 79 mg/l

12.2. Persistence and degradability

Carb & EGR Cleaner	
Persistence and degradability	Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Carb & EGR Cleaner		
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
Carbon dioxide (CO2) (124-38-9)		
Partition coefficient n-octanol/water (Log Pow)	0,83	
butanone; ethyl methyl ketone (78-93-3)		
Partition coefficient n-octanol/water (Log Pow)	0,3	
cyclohexane (110-82-7)		
Partition coefficient n-octanol/water (Log Pow)	3,4	
acetone; propan-2-one; propanone (67-64-1)		
Partition coefficient n-octanol/water (Log Pow)	-0,24	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Carb & EGR Cleaner	
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Carb & EGR Cleaner	
Other information	No other effects known
Global warming potential (GWP)	0.06 (Fluorinated greenhouse gases - (EC) No 2024/573)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

02/09/2024 (Revision date) BE - en 13/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

European List of Waste (LoW, EC 2000/532)

: According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
4.1. UN number or ID n	number			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
ransport document descr	ription			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.º ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
**************************************	2	22	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	zards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11
Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

02/09/2024 (Revision date) BE - en 14/18

Safety Data Sheet

Stowage and handling (IMDG)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

: SW1, SW22

Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
Stowage category (IMDG) : None

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : MP9

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 715 g/l

Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

Safety Data Sheet

Abbreviations and acronyms:	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.