

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/02/2025 Revision date: 05/02/2025 Supersedes version of: 06/06/2024 Version: 2.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

 Product name
 : Assembly Paste

 UFI
 : H220-F9CX-K00C-1432

 Product code
 : UDS000306AE

Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Main use category : Professional use Use of the substance/mixture : lubricants

#### 1.3. Details of the supplier of the safety data sheet

#### Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11, F +32(0)52/45.00.34

hse@crcind.com, www.crcind.com

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Aspiration hazard, Category 1 H304 Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



: Danger





GHS02

GHS07

GHS09

Signal word (CLP)

Contains : Hydrocarbons C7-C9,isoalkanes Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

Precautionary statements (CLP)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

: P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing mist, spray, vapours.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50  $^{\circ}$ C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

Contains PBT substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	O,O,O-triphenyl phosphorothioate (597-82-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	O,O,O-triphenyl phosphorothioate (597-82-0)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	50 – 75	Flam. Gas 1, H220 Press. Gas (Comp.), H280
White mineral oil (petroleum) substance with national workplace exposure limit(s) (BE)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078- 27	10 – 25	Asp. Tox. 1, H304
Hydrocarbons C7-C9,isoalkanes substance with national workplace exposure limit(s) (BE)	EC-No.: 921-728-3 REACH-no: 01-2119471305- 42	10 – 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Calcium carbonate substance with national workplace exposure limit(s) (BE)	CAS-No.: 1317-65-3 EC-No.: 215-279-6	5 – 10	Not classified

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium sulfate substance with national workplace exposure limit(s) (BE)	CAS-No.: 7778-18-9 EC-No.: 231-900-3 REACH-no: 01-2119444918- 26	1 – 5	Not classified
O,O,O-triphenyl phosphorothioate substance listed on REACH Candidate List PBT substance	CAS-No.: 597-82-0 EC-No.: 209-909-9 REACH-no: 01-2119979545- 21	< 0,25	Aquatic Chronic 1, H410

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Seek medical attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after ingestion : Risk of lung oedema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

## 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good

industrial hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## National occupational exposure and biological limit values

# Hydrocarbons C7-C9,isoalkanes

#### **Belgium - Occupational Exposure Limits**

OEL TWA 1400 mg/m<sup>3</sup>

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons C7-C9,isoalkanes	
	300 ppm
Calcium carbonate (1317-65-3)	
Belgium - Occupational Exposure Limits	
Local name	Calcium (carbonate de) # Calciumcarbonaat
OEL TWA	10 mg/m³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
White mineral oil (petroleum) (8042-47-5	5)
Belgium - Occupational Exposure Limits	
Local name	Huiles minérales (brouillards) # Olie (minerale-; nevel)
OEL TWA	5 mg/m³
OEL STEL	10 mg/m³
<b>5</b>	Koninklijk besluit/Arrêté royal 16/11/2023
crude oil. It consists of hydrocarbons ha	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 80°C (– 40°F to 176°F).] (68476-85-7)
Petroleum gases, liquefied; Petroleum g	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (- 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (- 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name OEL TWA	pas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (– 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bienètre au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name OEL TWA	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (– 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name OEL TWA  Remark  Regulatory reference  Calcium sulfate (7778-18-9)	gas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (– 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name OEL TWA  Remark  Regulatory reference  Calcium sulfate (7778-18-9)  Belgium - Occupational Exposure Limits	pas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (– 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bien- être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.
Petroleum gases, liquefied; Petroleum g crude oil. It consists of hydrocarbons ha in the range of approximately– 40°C to 8 Belgium - Occupational Exposure Limits Local name	pas; [A complex combination of hydrocarbons produced by the distillation of aving carbon numbers predominantly in the range of C3 through C7 and boiling 30°C (– 40°F to 176°F).] (68476-85-7)  Pétrole (gaz liquéfié) # LPG  1826 mg/m³  1000 ppm  C: la mention "C" signifie que l'agent en question relève du champ d'application du titre relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.  Koninklijk besluit/Arrêté royal 16/11/2023

## DNEL and PNEC

Hydrocarbons C7-C9,isoalkanes	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation 2035 mg/m³	
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m³
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

O,O,O-triphenyl phosphorothioate (597-82-	.0)
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,39 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,34 mg/m³
Long-term - systemic effects, dermal	0,2 mg/kg bodyweight/day
PNEC (Soil)	
PNEC soil	2,46 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
White mineral oil (petroleum) (8042-47-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	217,05 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	164,56 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	34,78 mg/m³
Long-term - systemic effects, dermal	93,02 mg/kg bodyweight/day

#### 8.2. Exposure controls

#### Appropriate engineering controls

### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Personal protection equipment

## Personal protective equipment symbol(s):





#### Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

#### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

## **Respiratory protection**

## Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

#### **Environmental exposure controls**

#### **Environmental exposure controls:**

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid : White. Colour

**Appearance** : Propane/butane propelled liquid.

Molecular mass : Not available Odour Solvent. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point : 95 °C

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available Upper explosion limit : Not available . 7 °C Flash point : > 200 °C Auto-ignition temperature Decomposition temperature : Not available : Not applicable pΗ Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s at 20 °C Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 0,92 g/cm3 at 20 °C : 0,92 at 20 °C : Not available

Relative density Relative vapour density at 20°C Particle characteristics : Not applicable

#### 9.2. Other information

### Information with regard to physical hazard classes

% of flammable ingredients : 60 - 100 %

Other safety characteristics

Additional information : For aerosols data for the product without propellant.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

## 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Hydrocarbons C7-C9,isoalkanes	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	21 mg/l/4h

## O,O,O-triphenyl phosphorothioate (597-82-0)

LD50 oral rat	> 10000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight

### White mineral oil (petroleum) (8042-47-5)

1	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h

### Calcium sulfate (7778-18-9)

Calciani Canalis (1770 10 0)		
LD50 oral rat	> 2000 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	

pH: Not applicable

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not applicable

Respiratory or skin sensitisation

: Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity

: Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Calcium sulfate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

$\alpha$	) O_trinhanyl	phosphorothioate	/507_82_N\
Ο, ι	,o-u ipileliyi	phosphorothioate	(331-02-0)

NOAEL (animal/male, F0/P) 300 mg/kg bodyweight	
NOAEL (animal/female, F0/P)	1000 mg/kg bodyweight
NOAEL (animal/male, F1)	300 mg/kg bodyweight
NOAEL (animal/female, F1)	1000 mg/kg bodyweight

STOT-single exposure : May cause drowsiness or dizziness.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons C7-C9,isoalkanes		
May cause drowsiness or dizziness.		
Not classified (Based on available data, the classification criteria are not met)		
Calcium sulfate (7778-18-9)		
237 mg/kg bodyweight		
May be fatal if swallowed and enters airways.		
Aerosol		
< 20,5 mm²/s at 20 °C		
Hydrocarbons C7-C9,isoalkanes		
0,5 mm²/s		
White mineral oil (petroleum) (8042-47-5)		
< 20,5 mm²/s		

## 11.2. Information on other hazards

#### **Endocrine disrupting properties**

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 12: Ecological information**

## 12.1. Toxicity

: Toxic to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects. (chronic)

(anishio)		
Hydrocarbons C7-C9,isoalkanes		
LC50 - Fish [1]	18,4 mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	2,4 mg/l Daphnia magna	
EC50 72h - Algae [1]	29 mg/l Pseudokirchneriella subcapitata	
O,O,O-triphenyl phosphorothioate (597-82-0)		
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna	
White mineral oil (petroleum) (8042-47-5)		
LC50 - Fish [1]	> 100 mg/l	
EC50 - Crustacea [1]	> 100 mg/l	
NOEC chronic fish	> 1000 mg/l	

## 12.2. Persistence and degradability

Assembly Paste	
Persistence and degradability	Not established. No data is available on the degradability of this product.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 12.3. Bioaccumulative potential

## **Assembly Paste**

Partition coefficient n-octanol/water (Log Kow)

Not applicable

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (68476-85-7)

Partition coefficient n-octanol/water (Log Pow) 2,3

### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

Assembly Paste		
Results of PBT assessment Contains PBT substances ≥ 0.1% assessed in accordance with REACH Annex XI		
Component		
Substance(s) meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	O,O,O-triphenyl phosphorothioate (597-82-0)	
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	O,O,O-triphenyl phosphorothioate (597-82-0)	

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

#### 12.7. Other adverse effects

Assembly Paste	
Other information	No other effects known
Global warming potential (GWP)	1.80 (Fluorinated greenhouse gases - (EC) No 2024/573)

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
ransport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2. ENVIRONMENTALLY HAZARDOUS
4.3. Transport hazard of	class(es)			
2.1	2.1	2.1	2.1	2.1
¥2	2	2	2	2
4.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR):MP9Transport category (ADR):2Special provisions for carriage - Packages (ADR):V14Special provisions for carriage - Loading, unloading:CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

#### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

 Limited quantities (IMDG)
 : SP277

 Excepted quantities (IMDG)
 : E0

 Packing instructions (IMDG)
 : P207, LP200

Special packing provisions (IMDG) : PP87, L2
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

## Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU-Regulations**

### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

## **REACH Candidate List (SVHC)**

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: O,O,O-triphenyl phosphorothioate (EC 209-909-9, CAS 597-82-0)

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

## **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Indication of changes		
Section	Changed item	Comments
2.3	Additional information	Added
12.5	Additional information	Added

Abbreviations	and acronyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

Full text of H- and EUH-statements:		
Aerosol 1	Aerosol, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.