

<b>Productname :</b>	COM 400	<b>Creationdate :</b>	29.06.17 Version : 2.0
<b>Ref.Nr.:</b>	UDS000466_3_20170629 (EN)	<b>Replaces:</b>	UDS000466_20151013

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**COM 400**  
Bulk

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Release Agents

**1.3. Details of the supplier of the safety data sheet**

CRC Industries UK Ltd.  
Ambersil House - Wylds Road  
Castlefield Industrial Estate  
TA6 4DD Bridgwater Somerset  
United Kingdom  
Tel.: +44 1278 727200  
Fax.: +44 1278 425644  
E-mail : hse.uk@crcind.com

**1.4. Emergency telephone number**

(+44)(0)1278 72 7200 (office hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**





<b>Physical:</b>	Flammable liquid, category 2 Highly flammable liquid and vapour.
Classification is based on test data.	
<b>Health:</b>	Aspiration Hazard Category 1 May be fatal if swallowed and enters airways. Skin irritation, category 2 Causes skin irritation. Specific target organ toxicity - single exposure, category 3 May cause drowsiness or dizziness.
Classification based on calculation method.	
<b>Environment:</b>	Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.
Classification based on calculation method.	
<b>Other hazards :</b>	Contains:

<b>Productname :</b>	COM 400	<b>Creationdate :</b>	29.06.17 Version : 2.0
<b>Ref.Nr.:</b>	UDS000466_3_20170629 (EN)	<b>Replaces:</b>	UDS000466_20151013

<b>Other hazards :</b>	Siloxanes/silicones silyl-oxy-terminat. May produce an allergic reaction. Not classified
------------------------	--

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

<b>Product identifier:</b>	Contains: Alkanes, C7-10-iso- Naphtha (petroleum), light alkylate; Low boiling point modified naphtha Siloxanes/silicones silyl-oxy-terminat.
<b>Hazard pictogram(s):</b>	   
<b>Signal word:</b>	Danger
<b>Hazard statement(s):</b>	H225 : Highly flammable liquid and vapour. H304 : May be fatal if swallowed and enters airways. H315 : Causes skin irritation. H336 : May cause drowsiness or dizziness. H411 : Toxic to aquatic life with long lasting effects.
<b>Precautionary statement(s):</b>	P101 : If medical advice is needed, have product container or label at hand. P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 : Use only outdoors or in a well-ventilated area. P301/310 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 : Do NOT induce vomiting. P405 : Store locked up. P501-2 : Dispose of contents/container to an authorised waste collection point.
<b>Supplemental Hazard information:</b>	Contains: Siloxanes/silicones silyl-oxy-terminat. May produce an allergic reaction.

## 2.3. Other hazards

No information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
----------------------	---------------------	---------	-------	-------	---------------------------	------------------	-------

**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

Alkanes, C7-10-iso-	-	90622-56-3	292-458-5	60-100	Flam. Liq. 2, Asp. Tox. 1, C50S, STOT SE 3, Aquatic Chronic 2	H225,H304,H315,H336,H411	B
Naphtha (petroleum), light alkylate; Low boiling point modified naphtha	01-2119463272-43	64741-66-8	265-068-8	20-40	Flam. Liq. 2, Asp. Tox. 1	H225,H304	
Siloxanes/silicones silyl-oxy-terminat.	-	14324771-92-5	481-810-5	<1	Flam. liq. 1, Pyr. Liq. 1, Water-react. 1, Acute Tox. 4, STOT SE 3, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1	H224,H250,H260,H332,H335,H315,H318,H317	

**Explanation notes**

B : substance with national established workplace exposure limit

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Contact with eyes :</b>	If substance has got into eyes, immediately wash out with water for at least 15 minutes Seek medical attention if irritation persists
<b>Contact with skin :</b>	Remove contaminated clothing immediately and wipe affected skin with dry cloth. Then wash with soap and water Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	Irritating to skin Symptoms : redness and pain
<b>Eye contact :</b>	Mildly irritating to eyes Symptoms : redness and pain

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>General Advice :</b>	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---

## SECTION 5: Firefighting measures

**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

### 5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures  
Forms hazardous decomposition products  
CO,CO<sub>2</sub>

### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing including eye/face protection.

### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses  
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material  
Place in appropriate container  
This material and/or its container must be disposed of as hazardous waste.

### 6.4. Reference to other sections

For further information see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation

<b>Productname :</b>	COM 400	<b>Creationdate :</b>	29.06.17 Version : 2.0
<b>Ref.Nr.:</b>	UDS000466_3_20170629 (EN)	<b>Replaces:</b>	UDS000466_20151013

Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.  
Keep out of reach of children.

## 7.3. Specific end use(s)

Release Agents

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Exposure limits :

No information available

## 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices.
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>hands and skin :</b>	When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	Nitrile
<b>eyes :</b>	Wear safety eyewear according to EN 166.

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

<b>Apperance : physical state :</b>	Liquid.
<b>colour :</b>	Colorless.
<b>odour :</b>	Aromatic.

**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

**pH :** Not available.  
**Boiling point/range :** >112 °C  
**Flash point :** 7 °C (Closed Cup)  
**Evaporation rate :** Not available.  
**Explosion limits : upper limit :** 6.2 %  
**lower limit :** 0.7 %  
**Vapour pressure :** Not available.  
**Relative density :** 0.720 g/cm3 (@ 20°C).  
**Solubility in water :** Immiscible with water  
**Auto-ignition :** >285 °C  
**Viscosity :** Not available.

## 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO2

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**acute toxicity:** based on available data the classification criteria are not met  
**skin corrosion/irritation:** Causes skin irritation.  
**serious eye damage/irritation:** based on available data the classification criteria are not met

**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

<b>respiratory or skin sensitisation:</b>	based on available data the classification criteria are not met
<b>germ cell mutagenicity:</b>	based on available data the classification criteria are not met
<b>carcinogenicity:</b>	based on available data the classification criteria are not met
<b>toxicity for reproduction:</b>	based on available data the classification criteria are not met
<b>STOT-single exposure:</b>	May cause drowsiness or dizziness.
<b>STOT repeated exposure:</b>	based on available data the classification criteria are not met
<b>aspiration hazard:</b>	May be fatal if swallowed and enters airways.

**Information on likely routes of exposure:**

<b>Inhalation :</b>	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
<b>Skin contact :</b>	Irritating to skin
<b>Eye contact :</b>	May cause irritation.

**Toxicological data :**

No information available

**SECTION 12: Ecological information****12.1. Toxicity**

Hazardous to the aquatic environment, chronic category 2  
Toxic to aquatic life with long lasting effects.

**Ecotoxicological data:**

No information available

**12.2. Persistence and degradability**

No information available

**12.3. Bioaccumulative potential**

No information available

**12.4. Mobility in soil**

Immiscible with water

**12.5. Results of PBT and vPvB assessment**

No information available



**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

#### 12.6. Other adverse effects

No information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations :** Disposal should be in accordance with local, state or national legislation

### SECTION 14: Transport information

#### 14.1. UN number

UN-number : 1866

#### 14.2. UN proper shipping name

Proper shipping name: RESIN SOLUTION, flammable

#### 14.3. Transport hazard class(es)

Class: 3  
ADR/RID - Classification code: F1

#### 14.4. Packing group

Packing group: II

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: Yes

IMDG - Marine pollutant: Marine pollutant

IATA/ICAO - Environmentally hazardous: Yes

#### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D/E)

IMDG - Ems: F-E, S-E

IATA/ICAO - PAX: 353

IATA/ICAO - CAO: 364



**Productname :** COM 400  
**Ref.Nr.:** UDS000466\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 2.0  
**Replaces:** UDS000466\_20151013

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Regulation (EC) No 1907/2006 (REACH)  
Regulation (EC) No 1272/2008 (CLP)

#### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation hazard statements: H224 : Extremely flammable liquid and vapour.  
H225 : Highly flammable liquid and vapour.  
H250 : Catches fire spontaneously if exposed to air.  
H260 : In contact with water releases flammable gases which may ignite spontaneously.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : 8.2. Exposure controls  
acronyms and synonyms: TWA = time weight average  
STEL = short time exposure limit  
VOC = volatile organic compounds  
PBT = persistant bioaccumulative toxic  
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.