

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/02/2025 Revision date: 10/06/2024 Supersedes version of: 21/06/2023 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Crick 130

UFI : 8KQX-0806-N00A-J7MW

Product code : UDS000719AE Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use

Use of the substance/mixture : Welding and soldering agents

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.

Touwslagerstraat 1

9240 Zele Belgium

T +32(0)52/45.60.11, F +32(0)52/45.00.34

hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Contains : propan-2-ol; isopropyl alcohol; isopropanol;acetone; propan-2-one; propanone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

EUH-statements

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	25 – 50	Flam. Gas 1, H220 Press. Gas (Comp.), H280
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Talc (Mg3H2(SiO3)4) substance with national workplace exposure limit(s) (BE)	CAS-No.: 14807-96-6 EC-No.: 238-877-9 REACH-no: 01-2120140278- 58	5 – 10	Not classified

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

10/06/2024 (Revision date) BE - en 2/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical

attention if irritation develops.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

10/06/2024 (Revision date) BE - en 3/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
Belgium - Occupational Exposure Limits		
Local name	Alcool isopropylique # Isopropylalcohol	
OEL TWA	500 mg/m³	
	200 ppm	
OEL STEL	1000 mg/m³	
	400 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
Talc (Mg3H2(SiO3)4) (14807-96-6)		
Belgium - Occupational Exposure Limits		
Local name	Talc (sans fibre d'amiante, poussières alvéolaires) # Talk (asbestvrij, inadembaar stof)	
OEL TWA	2 mg/m³	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
acetone; propan-2-one; propanone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA	1210 mg/m³	
	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)	
Belgium - Occupational Exposure Limi	ts
Local name	Acétone # Aceton
OEL TWA	594 mg/m³
	246 ppm
OEL STEL	1187 mg/m³
	492 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

Local name	Pétrole (gaz liquéfié) # LPG
OEL TWA	1826 mg/m³
	1000 ppm
Remark	C: la mention "C" signifie que l'agent en question relève du champ d'application du titre 2 relatif aux agents cancérigènes, mutagènes et reprotoiques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

DNEL and PNEC

DNEL and PNEC			
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)			
DNEL/DMEL (Workers)	DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	500 mg/m³		
DNEL/DMEL (General population)	DNEL/DMEL (General population)		
Long-term - systemic effects,oral	26 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	89 mg/m³		
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	140,9 mg/l		
PNEC aqua (marine water)	140,9 mg/l		
PNEC aqua (intermittent, freshwater)	140,9 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	552 mg/kg dwt		
PNEC sediment (marine water)	552 mg/kg dwt		
PNEC (Soil)			
PNEC soil	28 mg/kg dwt		
PNEC (Oral)			
PNEC oral (secondary poisoning)	160 mg/kg food		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isoprop	anol (67-63-0)	
PNEC (STP)		
PNEC sewage treatment plant	2251 mg/l	
acetone; propan-2-one; propanone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10,6 mg/l	
PNEC aqua (marine water)	1,06 mg/l	
PNEC aqua (intermittent, freshwater)	21 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	30,4 mg/kg dwt	
PNEC sediment (marine water)	3,04 mg/kg dwt	
PNEC (Soil)		
PNEC soil	29,5 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : White.

Appearance : Propane/butane propelled liquid.

Odour : Solvent.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit : Not available Upper explosion limit : Not available : Not applicable Flash point : Not available Auto-ignition temperature : Not available Decomposition temperature : Not applicable pН : Not available Viscosity, kinematic Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 0,885 g/cm3 at 20 °C Relative density : 0,885 at 20 °C Relative vapour density at 20°C : Not available

9.2. Other information

Particle characteristics

Information with regard to physical hazard classes

% of flammable ingredients : 75 - 100 %

Other safety characteristics

VOC content : 630 g/l

Additional information : For aerosols data for the product without propellant.

: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

Vaporizer

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (iiiiaiation)	. Not classified (based on available data, the classification chiefla are not met)
propan-2-ol; isopropyl alcohol; isoprop	panol (67-63-0)
LD50 oral rat	5840 mg/kg bodyweight
Talc (Mg3H2(SiO3)4) (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
acetone; propan-2-one; propanone (67	-64-1)
LD50 oral rat	5800 mg/kg bodyweight
LD50 dermal	> 15688 mg/kg bodyweight
LC50 Inhalation - Rat	76 mg/l/4h
Skin corrosion/irritation	 Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) STOT-single exposure May cause drowsiness or dizziness. acetone; propan-2-one; propanone (67-64-1) STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met) **Aspiration hazard** : Not classified (Based on available data, the classification criteria are not met) Crick 130 Aerosol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term : Not classified (Based on available data, the classification criteria are not met)

(acute)
Hazardous to the aquatic environment, long-term

: Not classified (Based on available data, the classification criteria are not met)

(chronic)

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	10000 mg/l
LC50 - Fish [2]	9640 mg/l
Talc (Mg3H2(SiO3)4) (14807-96-6)	
LC50 - Fish [1]	89581,02 mg/l
LC50 - Fish [2]	110000 mg/l
EC50 96h - Algae [1]	7202,7 mg/l

	propan-2-one;		(C7 C4 4)	
acetone,	propari-z-one,	propanone	(07-04-1)	1

acetone; propan-z-one; propanone (67-64-1)	
LC50 - Fish [1]	5540 mg/l
EC50 - Other aquatic organisms [1]	12600 mg/l Daphnia magna (Water flea)
LOEC (chronic)	> 79 mg/l
NOEC (chronic)	≥ 79 mg/l

12.2. Persistence and degradability

Crick 130

NOEC (chronic)

Persistence and degradability Not established. No data is available on the degradability of this product.

1459,798 mg/l 30 d

12.3. Bioaccumulative potential

Crick 130

Partition coefficient n-octanol/water (Log Kow) Not applicable

acetone; propan-2-one; propanone (67-64-1)

Partition coefficient n-octanol/water (Log Pow) -0,24

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (68476-85-7)

Partition coefficient n-octanol/water (Log Pow) 2,3

10/06/2024 (Revision date) BE - en 9/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Crick 130	
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Crick 130		
Other information	No other effects known	
Global warming potential (GWP)	1.50 (Fluorinated greenhouse gases - (EC) No 2024/573)	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

n accordance with ADR / IMI	DG / IATA / ADIN / RID			
ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	number			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	ription			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
5. Environmental ha	azards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN)

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

: 1

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 630 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations ar	nd acronyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:			
Aerosol 1	Aerosol, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1	Flammable gases, Category 1		
Flam. Liq. 2	Flammable liquids, Category 2		
Press. Gas (Comp.)	Gases under pressure : Compressed gas		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
EUH066	Repeated exposure may cause skin dryness or cracking.		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.