Regulation EC No 1907/2006 Art.31

Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982 20170322
		Ropidoool	BBCCCCCCCONCCC

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### FAST DRY DEGREASER Bulk

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

### 1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba Touwslagerstraat 1 9240 Zele Belgium Tel.: +32(0)52/45.60.11 Fax.: +32(0)52/45.00.34 E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
<b>CRC Industries France</b>	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTR. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

### 1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Physical:

Flammable liquid, category 2

Highly flammable liquid and vapour.

Classification is based on test data. Health: Skin irritation, category 2



**CRC Industries Europe bvba** Touwslagerstraat 1, 9240 Zele – Belgium Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

fety Data Sheet			Regulation EC No 1907/2006 Art.31		
ictname : r.:	FAST DRY DEGRI BDS000982_3_20		Creationdate : Replaces:	29.06.17 Version : 3.0 BDS000982_20170322	
Environm		Specific targe May cause d Aspiration Ha May be fatal on method. Hazardous to Toxic to aqua	, category 2 bus eye irritation. et organ toxicity - single rowsiness or dizziness azard Category 1 if swallowed and enter	s airways. ent, chronic category 2	
Classification based on calculation method. Other hazards : Not classified		ł			
abel elem	ents				
lling accor Product io	ding to Regulation ( dentifier:	Contains:			
Product id					
Product id	dentifier: ctogram(s):	Contains: hydrocarbons	s (1)		
Product id Hazard pi Signal wo	dentifier: ctogram(s):	Contains: hydrocarbons Danger H225 : Highly H315 : Cause H319 : Cause H336 : May c H304 : May b	s y flammable liquid and es skin irritation. es serious eye irritatior cause drowsiness or di be fatal if swallowed an	n. zziness. d enters airways.	
Product id Hazard pi Signal wo Hazard st	dentifier: ctogram(s): ord:	Contains: hydrocarbons Danger H225 : Highly H315 : Cause H319 : Cause H336 : May c H304 : May b H411 : Toxic P102 : Keep	s y flammable liquid and es skin irritation. es serious eye irritatior cause drowsiness or di be fatal if swallowed an to aquatic life with long out of reach of children	n. zziness. d enters airways. g lasting effects.	

Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons> 30 %

### 2.3. Other hazards

No information available

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances



P501-2 : Dispose of contents/container to an authorised waste collection point.

P405 : Store locked up.

Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322

### Not applicable.

## 3.2. Mixtures

Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C7, n- alkanes,isoalkanes, cyclic	01- 2119475515- 33	-	(927- 510-4)		Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	Q
Hydrocarbons, C6-C7, n- alkanes,isoalkanes,cyclics,< 5% n- hexane	01- 2119475514- 35	-	(921- 024-6)		Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	B,Q
propan-2-ol; isopropyl alcohol ;isopropanol	01- 2119457558- 25	67- 63-0	200- 661-7	5-10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	в
acetone; propan-2-one; propanone	01- 2119471330- 49	67- 64-1	200- 662-2	5-10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A
hydrocarbons,C6,isoalkanes,< 5% n- hexane	01- 2119484651- 34	-	(931- 254-9)	5-10	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	Q
Explanation notes							
A : substance with Community workplace exposure limit							

B : substance with national established workplace exposure limit

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(\* Explanation phrases : see chapter 16)

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

Contact with eyes :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Contact with skin :	Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Inhalation :	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
Ingestion :	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	Irritating to skin Symptoms : redness and pain

CR®	<b>CRC Industries Europe byba</b> Touwslagerstraat 1, 9240 Zele – Belgium Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com	3 / 10
-----	--	--------

Regulation EC No 1907/2006 Art.31

Eye contact :	Irritating to eyes
	Symptoms : redness and pain, impaired vision

### 4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures Forms hazardous decomposition products CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing including eye/face protection.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

### 6.4. Reference to other sections

For further information see section 8

## SECTION 7: Handling and storage



Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges Equipment should be earthed Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection. Eyewash bottles should be available

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place. Keep out of reach of children.

#### 7.3. Specific end use(s)

Cleaners - Heavy duty

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Exposure limits :**

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
National established exposure limits, United Kingdom			
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm

#### 8.2. Exposure controls

Control procedures :	Ensure adequate ventilation
	Keep away from heat and sources of ignition
	Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product.
	It is good practice to wear gloves and to provide adequate ventilation whenever



Safety Data Sheet		Regulation EC No 1907/2006 Art.31	
Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322

inhalation :	using the product. In all cases handle and use the product in accordance with good industrial hygiene practices. In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equiped with organic gas/vapor cartridge (type AX)
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	(neoprene)
	The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time.
eyes :	Wear safety eyewear according to EN 166.
Environmental protection:	Avoid release to the environment. Collect spillage.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Apperance : physical state :	Liquid.
colour :	Colorless.
odour :	Solvent.
pH :	Not applicable.
Boiling point/range :	56-99 °C
Flash point :	- 26 °C
Evaporation rate :	2.8 (Ether=1)
Explosion limits : upper limit :	Not available.
lower limit :	Not available.
Vapour pressure :	Not available.
Relative density :	0.714 g/cm3 (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 200 °C
Viscosity :	Not available.

### 9.2. Other information

VOC = volatile organic compounds 715 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0	
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322	

No hazardous reactions known if used for its intended purpose

#### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

#### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO2

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	Causes skin irritation.
serious eye damage/irritation:	Causes serious eye irritation.
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	May cause drowsiness or dizziness.
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	May be fatal if swallowed and enters airways.

### Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Irritating to skin
Eye contact :	Irritating to eyes

Toxicological data :



Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	5840 mg/kg
		LC50 inhal.rat	> 25000 mg/l
		LD50 derm.rabit	13900 mg/kg
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5800 mg/kg
		LC50 inhal.rat	76 mg/l
		LD50 derm.rabit	> 15800 mg/kg
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	-	LD50 oral rat	> 5840 mg/kg
		LC50 inhal.rat	23.3 mg/l
		LD50 derm.rat	> 2920 mg/kg
hydrocarbons,C6,isoalkanes,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 3000 mg/kg

# SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.

### Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	1000 mg/l
		LC50 fish	9640 mg/l
		EC50 daphnia	9714 mg/l
acetone; propan-2-one; propanone	67-64-1	IC50 algae	530 mg/l
		LC50 fish	5540 mg/l
		EC50 daphnia	8800 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	-	IC50 algae	10-30 mg/l
		LC50 fish	> 13.4 mg/l
		EC50 daphnia	3 mg/l
hydrocarbons,C6,isoalkanes,< 5% n-hexane	-	IC50 algae	55 mg/l
		LC50 fish	> 1 mg/l
		EC50 daphnia	3.87 mg/l

## 12.2. Persistence and degradability

No experimental data available



Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322

#### 12.3. Bioaccumulative potential

No experimental data available

#### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No experimental data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product :	This material and its container must be disposed of in a safe way.	
	Do not discharge into drains or the environment, dispose to an authorised waste collection point.	
Contaminated packaging :	Disposal should be in accordance with local, state or national legislation	

# **SECTION 14: Transport information**

## 14.1. UN number

UN-number: 1993

### 14.2. UN proper shipping name

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (naphta, acetone)

### 14.3. Transport hazard class(es)

Class: 3 ADR/RID - Classification code: F1

### 14.4. Packing group

Packing group: II

### 14.5. Environmental hazards

ADR/RID - Environmentally Yes hazardous:



Productname :	FAST DRY DEGREASER	Creationdate :	29.06.17 Version : 3.0
Ref.Nr.:	BDS000982_3_20170629 (EN)	Replaces:	BDS000982_20170322

IMDG - Marine pollutant: Marine pollutant IATA/ICAO - Environmentally hazardous: Yes

### 14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D/E)
IMDG - Ems:	F-E, S-E
IATA/ICAO - PAX:	353
IATA/ICAO - CAO	364

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP)

### 15.2. Chemical safety assessment

No information available

## **SECTION 16: Other information**

*Explanation hazard statements:	<ul> <li>H225 : Highly flammable liquid and vapour.</li> <li>H304 : May be fatal if swallowed and enters airways.</li> <li>H315 : Causes skin irritation.</li> <li>H319 : Causes serious eye irritation.</li> <li>H336 : May cause drowsiness or dizziness.</li> <li>H411 : Toxic to aquatic life with long lasting effects.</li> </ul>
REVISIONS IN CHAPTRE :	8.2. Exposure controls
acronyms and synonyms:	TWA = time weight average STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

