

Productname : GASKET REMOVER PRO      Creationdate : 13.03.19 Version : 2.0  
 Ref.Nr.: BDS002248\_3\_20190313 (EN)      Replaces: BDS002248\_20181115

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**GASKET REMOVER PRO**  
Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

### 1.3. Details of the supplier of the safety data sheet

**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele  
Belgium  
Tel.: +32(0)52/45.60.11  
Fax.: +32(0)52/45.00.34  
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Smedsgatan 3-5 LT4, PL62, 08101 LOJO	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

### 1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosol, category 2  
 Flammable aerosol.  
 Pressurised container: May burst if heated.

Classification is based on test data.



<b>Productname :</b>	GASKET REMOVER PRO	<b>Creationdate :</b>	13.03.19 Version : 2.0
<b>Ref.Nr.:</b>	BDS002248_3_20190313 (EN)	<b>Replaces:</b>	BDS002248_20181115

**Health:** Carcinogenicity, category 2  
Suspected of causing cancer .  
Skin irritation, category 2  
Causes skin irritation.  
Eye irritation, category 2  
H316  
Specific target organ toxicity - single exposure, category 3  
May cause drowsiness or dizziness.

Classification based on calculation method.

**Environment:** Hazardous to the aquatic environment, chronic category 3  
Harmful to aquatic life with long lasting effects.

Classification based on calculation method.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

**Product identifier:** Contains:  
dichloromethane; methylene chloride

**Hazard pictogram(s):**



**Signal word:** Warning

**Hazard statement(s):** H223 : Flammable aerosol.  
H229 : Pressurised container: May burst if heated.  
H351 : Suspected of causing cancer .  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.  
H412 : Harmful to aquatic life with long lasting effects.

**Precautionary statement(s):** P102 : Keep out of reach of children.  
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 : Do not spray on an open flame or other ignition source.  
P251 : Do not pierce or burn, even after use.  
P201 : Obtain special instructions before use.  
P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 : Use only outdoors or in a well-ventilated area.  
P280 : Wear protective gloves/protective clothing/eye protection/face protection.  
P308/313 : IF exposed or concerned: Get medical advice/attention.  
P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501-2 : Dispose of contents/container to an authorised waste collection point.

**Regulation (EC) No 648/2004 on detergents:** aromatic hydrocarbons 5 - 15 %  
halogenated hydrocarbons > 30 %

## 2.3. Other hazards

The product does not contain any PBT or vPvB substances.

Productname : GASKET REMOVER PRO      Creationdate : 13.03.19 Version : 2.0  
 Ref.Nr.: BDS002248\_3\_20190313 (EN)      Replaces: BDS002248\_20181115

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dichloromethane; methylene chloride	01-2119480404-41	75-09-2	200-838-9	50-75	Carc. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3	H351,H315,H319,H336	
ethanol; ethyl alcohol	01-2119457610-43	64-17-5	200-578-6	5-10	Flam. Liq. 2, Eye Irrit. 2	H225,H319	B,X,W
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	01-2119485926-20	68512-91-4	270-990-9	5-10	Press. Gas, Flam. Gas 1	H280,H220	K,G
Hydrocarbons, C10, aromatics,	01-2119463583-34	-	(918-811-1)	5-10	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H336,H304,H411	Q
propan-2-ol; isopropyl alcohol ;isopropanol	01-2119457558-25	67-63-0	200-661-7	<1	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	B
butanone; ethyl methyl ketone	01-2119457290-43	78-93-3	201-159-0	<1	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A

#### Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

W : Note: substance mentioned on the list of CMR-substances of the Dutch Ministry of Social Affairs and Employment (SZW)

X : SCL (specific concentration limit)in accordance with art.10 of CLP Regulation No 1272/2008

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Contact with eyes :</b>	If substance has got into eyes, immediately wash out with plenty of water Seek medical advice
<b>Contact with skin :</b>	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. If breathing is difficult give oxygen Apply artificial respiration only if patient is not breathing Seek immediate medical attention
<b>Ingestion :</b>	Do not induce vomiting Rinse mouth with water (do not swallow)



**Productname :** GASKET REMOVER PRO      **Creationdate :** 13.03.19 Version : 2.0  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN)      **Replaces:** BDS002248\_20181115

..... If swallowed seek medical advice immediately and show this container or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	May cause irritation. High concentrations may cause narcotic effects. Symptoms : sore throat, cough, shortness of breath, severe breathing difficulties, headache
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : abdominal pain, dizziness, diarrhea, cough, headache
<b>Skin contact :</b>	May cause irritation. Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis Symptoms : redness and pain
<b>Eye contact :</b>	May cause irritation. Symptoms : redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>General Advice :</b>	If any symptoms should occur, seek medical advice. If you feel unwell, seek medical advice (show the label where possible) Methylene chloride is classified as carcinogenic Cat.2 In case of repeated exposures, regular medical examination is advised
-------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO<sub>2</sub>,HCl  
chlorinated compounds

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes  
Substance evolves toxic fumes, wear self-contained breathing apparatus

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources



**Productname :** GASKET REMOVER PRO  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN)  
**Creationdate :** 13.03.19 Version : 2.0  
**Replaces:** BDS002248\_20181115

Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

## 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

## 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material  
Wash spill site with water and detergent

## 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Keep in a cool, dry, well ventilated place  
Keep out of reach of children.

## 7.3. Specific end use(s)

Cleaners - Heavy duty

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Exposure limits :

Hazardous ingredient

CAS-nr. method



**Productname :** GASKET REMOVER PRO **Creationdate :** 13.03.19 Version : 2.0  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN) **Replaces:** BDS002248\_20181115

EU established exposure limits:			
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
dichloromethane; methylene chloride	75-09-2	TWA	100 ppm
		STEL	200 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm
National established exposure limits, United Kingdom			
ethanol; ethyl alcohol	64-17-5	TWA	1000 ppm
		STEL	500 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
dichloromethane; methylene chloride	75-09-2	TWA	100 ppm
		STEL	300 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm
National established exposure limits, Ireland			
ethanol; ethyl alcohol	64-17-5	STEL	1000 ppm
		TWA	200 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	200 ppm
		STEL	400 ppm
dichloromethane; methylene chloride	75-09-2	TWA	50 ppm
		STEL	-
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm

## 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type AX)
<b>hands and skin :</b>	Wear suitable protective gloves The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	(polyvinylalcohol)
<b>eyes :</b>	Wear safety eyewear according to EN 166.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

<b>Apperance : physical state :</b>	Liquid under pressure.
<b>colour :</b>	Colorless.
<b>odour :</b>	Solvent.
<b>pH :</b>	Not applicable.



**Productname :** GASKET REMOVER PRO  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN)  
**Creationdate :** 13.03.19 Version : 2.0  
**Replaces:** BDS002248\_20181115

**Boiling point/range :** Not available.  
**Flash point :** None  
**Evaporation rate :** Not available.  
**Explosion limits : upper limit :** Not available.  
**lower limit :** Not available.  
**Vapour pressure :** Not available.  
**Relative density :** 1.18 g/cm<sup>3</sup> (@ 20°C).  
**Solubility in water :** Insoluble in water  
**Auto-ignition :** > 200 °C  
**Viscosity :** 80 mPa.s (@ 20°C).

## 9.2. Other information

**VOC = volatile organic compounds** 1180 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO<sub>2</sub>,HCl  
traces of chlorine and phosgene

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects



**Productname :** GASKET REMOVER PRO **Creationdate :** 13.03.19 Version : 2.0  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN) **Replaces:** BDS002248\_20181115

**acute toxicity:** based on available data the classification criteria are not met  
**skin corrosion/irritation:** Causes skin irritation.  
**serious eye damage/irritation:** Causes serious eye irritation.  
**respiratory or skin sensitisation:** based on available data the classification criteria are not met  
**germ cell mutagenicity:** based on available data the classification criteria are not met  
**carcinogenicity:** Suspected of causing cancer .  
**toxicity for reproduction:** based on available data the classification criteria are not met  
**STOT-single exposure:** May cause drowsiness or dizziness.  
**STOT repeated exposure:** based on available data the classification criteria are not met  
**aspiration hazard:** based on available data the classification criteria are not met

#### Information on likely routes of exposure:

**Inhalation :** May cause irritation.  
High concentrations may cause narcotic effects.  
**Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.  
**Skin contact :** Irritating to skin  
**Eye contact :** Irritating to eyes

#### Toxicological data :

Hazardous ingredient	CAS-nr.	method	
ethanol; ethyl alcohol	64-17-5	LD50 oral rat	> 2000 mg/kg
		LD50 derm.rabit	> 2000 mg/kg
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	5840 mg/kg
		LC50 inhal.rat	> 25000 mg/l
		LD50 derm.rabit	13900 mg/kg
dichloromethane; methylene chloride	75-09-2	LD50 oral rat	> 2000 mg/kg
		LD50 derm.rat	> 2000 mg/kg
butanone; ethyl methyl ketone	78-93-3	LD50 oral rat	> 2000 mg/kg
Hydrocarbons, C10, aromatics,	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	4688 mg/m3
		LD50 derm.rabit	> 2000 mg/kg

May cause damage to organs through prolonged or repeated exposure .  
Methylene chloride is classified as carcinogenic Cat.2

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3  
Harmful to aquatic life with long lasting effects.

#### Ecotoxicological data:





**Productname :** GASKET REMOVER PRO  
**Ref.Nr.:** BDS002248\_3\_20190313 (EN)

**Creationdate :** 13.03.19 Version : 2.0  
**Replaces:** BDS002248\_20181115

Hazardous ingredient	CAS-nr.	method	
ethanol; ethyl alcohol	64-17-5	LC50 fish	> 100 mg/l
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	1000 mg/l
		LC50 fish	9640 mg/l
		EC50 daphnia	9714 mg/l
dichloromethane; methylene chloride	75-09-2	IC50 algae	> 662 mg/l
		LC50 fish	193 mg/l
		EC50 daphnia	27 mg/l
Hydrocarbons, C10, aromatics,	-	IC50 algae	> 10 mg/l
		LC50 fish	2-5 mg/l
		EC50 daphnia	3-10 mg/l

### 12.2. Persistence and degradability

No experimental data available

### 12.3. Bioaccumulative potential

no bioaccumulation expected

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

### 12.6. Other adverse effects

No experimental data available  
GWP (global warming potential): 7

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

## SECTION 14: Transport information

### 14.1. UN number

UN-number : 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS



Productname : GASKET REMOVER PRO      Creationdate : 13.03.19 Version : 2.0  
Ref.Nr.: BDS002248\_3\_20190313 (EN)      Replaces: BDS002248\_20181115

#### 14.3. Transport hazard class(es)

Class: 2.1  
Subsidiary risk: 6.1  
ADR/RID - Classification code: 5TF

#### 14.4. Packing group

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

#### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D, S-U

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Regulation (EC) No 1907/2006 (REACH)  
Regulation (EC) No 1272/2008 (CLP)  
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

#### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation hazard statements: H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.



---

<b>Productname :</b>	GASKET REMOVER PRO	<b>Creationdate :</b>	13.03.19 Version : 2.0
<b>Ref.Nr.:</b>	BDS002248_3_20190313 (EN)	<b>Replaces:</b>	BDS002248_20181115

---

H351 : Suspected of causing cancer .  
H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : 14.3. Transport hazard class(es)  
acronyms and synonyms: TWA = time weight average  
STEL = short time exposure limit  
VOC = volatile organic compounds  
PBT = persistant bioaccumulative toxic  
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.