

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

POLYMER REMOVER
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylids Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom
Tel.: +44 1278 727200
Fax.: +44 1278 425644
E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1
Extremely flammable aerosol.
Pressurised container: May burst if heated.

Classification is based on test data.

Health: Not classified

Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3
Harmful to aquatic life with long lasting effects.

Classification based on calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008



1 / 10

CRC Industries UK Limited
Ambersil House, Wylids Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

Hazard pictogram(s):

| | |
|---|---|
| Signal word: | Danger |
| Hazard statement(s): | H222 : Extremely flammable aerosol. H229 : Pressurised container: May burst if heated. H412 : Harmful to aquatic life with long lasting effects. |
| Precautionary statement(s): | P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 : Do not spray on an open flame or other ignition source. P251 : Do not pierce or burn, even after use. P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501-2 : Dispose of contents/container to an authorised waste collection point. |
| Supplemental Hazard information: | None |

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS-nr. | EC-nr | w/w % | Hazard Class and Category | Hazard statement | Notes |
|---|---------------------|----------|-------------|-------|---|--------------------------|-------|
| methylal | 01-2119664781-31 | 109-87-5 | 203-714-2 | 25-50 | Flam. Liq. 2 | H225 | B |
| dimethyl ether | 01-2119472128-37 | 115-10-6 | 204-065-8 | 25-50 | Flam. Gas 1, Press. Gas | H220,H280 | A |
| ethanol; ethyl alcohol | 01-2119457610-43 | 64-17-5 | 200-578-6 | 5-10 | Flam. Liq. 2, Eye Irrit. 2 | H225,H319 | B,X |
| Hydrocarbons, C10, aromatics, | 01-2119463583-34 | - | (918-811-1) | 1-5 | STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H336,H304,H411 | Q |
| methanol | 01-2119433307-44 | 67-56-1 | 200-659-6 | <3 | Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1 | H225,H331,H311,H301,H370 | A |
| propan-2-ol; isopropyl alcohol ;isopropanol | 01-2119457558-25 | 67-63-0 | 200-661-7 | <1 | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 | H225,H319,H336 | B |

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

X : SCL (specific concentration limit)in accordance with art.10 of CLP Regulation No 1272/2008

(* Explanation phrases : see chapter 16)

2 / 10

CRC Industries UK Limited

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD

Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| Contact with eyes : | If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention. |
| Contact with skin : | Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. |
| Inhalation : | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Ingestion : | If swallowed accidentally, do not induce vomiting and seek medical advice. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------------|---|
| Inhalation : | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting |
| Skin contact : | May cause irritation. Symptoms : redness and pain |
| Eye contact : | May cause irritation. Symptoms : redness and pain |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-------------------------|---|
| General Advice : | If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor |
|-------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures



3 / 10

CRC Industries UK Limited
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep in a cool, dry, well ventilated place
Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Heavy duty

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



4 / 10

CRC Industries UK Limited
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

Exposure limits :

| Hazardous ingredient | CAS-nr. | method | |
|---|----------|--------|----------|
| EU established exposure limits: | | | |
| dimethyl ether | 115-10-6 | TWA | 1000 ppm |
| methanol | 67-56-1 | TWA | 200 ppm |
| propan-2-ol; isopropyl alcohol ;isopropanol | 67-63-0 | TWA | 400 ppm |
| | | STEL | 500 ppm |
| National established exposure limits, United Kingdom | | | |
| methylal | 109-87-5 | TWA | 1000 ppm |
| | | STEL | 1250 ppm |
| dimethyl ether | 115-10-6 | TWA | 400 ppm |
| | | STEL | 500 ppm |
| ethanol; ethyl alcohol | 64-17-5 | TWA | 1000 ppm |
| methanol | 67-56-1 | TWA | 200 ppm |
| | | STEL | 250 ppm |
| propan-2-ol; isopropyl alcohol ;isopropanol | 67-63-0 | TWA | 400 ppm |
| | | STEL | 500 ppm |

8.2. Exposure controls

| | |
|--------------------------------------|---|
| Control procedures : | Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges |
| Personal protection : | Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation |
| inhalation : | In case of insufficient ventilation, wear suitable respiratory equipment. |
| recommended respiratory protection: | Air purifying respirator equipped with organic gas/vapor cartridge (type AX) |
| hands and skin : | When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. |
| Recommended gloves: | (polyvinylalcohol) |
| eyes : | Wear safety eyewear according to EN 166. |
| Environmental protection: | Avoid release to the environment. Collect spillage. |
| Consumer exposure protection: | Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)



5 / 10

CRC Industries UK Limited
 Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
 Somerset, TA6 4DD
 Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)
Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

Apperance : physical state : DME propelled liquid.
colour : White.
odour : Solvent.
pH : Not applicable.
Boiling point/range : Not available.
Flash point : - 18 °C (Closed Cup)
Evaporation rate : Not available.
Explosion limits : upper limit : Not available.
lower limit : Not available.
Vapour pressure : Not available.
Relative density : 0.878 g/cm³ (@ 20°C).
Solubility in water : Insoluble in water
Auto-ignition : > 200 °C
Viscosity : 700-1500 (thixotropic) mPa.s (@ 20°C).

9.2. Other information

VOC = volatile organic compounds 777 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

SECTION 11: Toxicological information



6 / 10

CRC Industries UK Limited
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

11.1. Information on toxicological effects

| | |
|---|---|
| acute toxicity: | based on available data the classification criteria are not met |
| skin corrosion/irritation: | based on available data the classification criteria are not met |
| serious eye damage/irritation: | based on available data the classification criteria are not met |
| respiratory or skin sensitisation: | based on available data the classification criteria are not met |
| germ cell mutagenicity: | based on available data the classification criteria are not met |
| carcinogenicity: | based on available data the classification criteria are not met |
| toxicity for reproduction: | based on available data the classification criteria are not met |
| STOT-single exposure: | based on available data the classification criteria are not met |
| STOT repeated exposure: | based on available data the classification criteria are not met |
| aspiration hazard: | based on available data the classification criteria are not met |

Information on likely routes of exposure:

| | |
|-----------------------|---|
| Inhalation : | Inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | May cause gastrointestinal disturbances |
| Skin contact : | Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis |
| | Repeated exposure may cause skin dryness or cracking. |
| Eye contact : | May cause irritation. |

Toxicological data :

| Hazardous ingredient | CAS-nr. | method | |
|---|----------|-----------------|--------------|
| methylal | 109-87-5 | LD50 oral rat | 6423 mg/kg |
| | | LD50 derm.rabit | > 5000 mg/kg |
| dimethyl ether | 115-10-6 | LC50 inhal.rat | 309 mg/l |
| | | | |
| ethanol; ethyl alcohol | 64-17-5 | LD50 oral rat | > 2000 mg/kg |
| | | LD50 derm.rabit | > 2000 mg/kg |
| propan-2-ol; isopropyl alcohol ;isopropanol | 67-63-0 | LD50 oral rat | 5840 mg/kg |
| | | LC50 inhal.rat | > 25000 mg/l |
| | | LD50 derm.rabit | 13900 mg/kg |
| Hydrocarbons, C10, aromatics, | - | LD50 oral rat | > 5000 mg/kg |
| | | LC50 inhal.rat | 4688 mg/m3 |
| | | LD50 derm.rabit | > 2000 mg/kg |

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3
 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:



7 / 10

CRC Industries UK Limited
 Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
 Somerset, TA6 4DD
 Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN)

Creationdate : 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

| Hazardous ingredient | CAS-nr. | method | |
|---|----------|--------------|-------------|
| methylal | 109-87-5 | LC50 fish | > 1000 mg/l |
| | | EC50 daphnia | > 1000 mg/l |
| dimethyl ether | 115-10-6 | IC50 algae | 154.9 mg/l |
| | | LC50 fish | 4.1 mg/l |
| | | EC50 daphnia | 4.4 mg/l |
| ethanol; ethyl alcohol | 64-17-5 | LC50 fish | > 100 mg/l |
| propan-2-ol; isopropyl alcohol ;isopropanol | 67-63-0 | IC50 algae | 1000 mg/l |
| | | LC50 fish | 9640 mg/l |
| | | EC50 daphnia | 9714 mg/l |
| Hydrocarbons, C10, aromatics, | - | IC50 algae | > 10 mg/l |
| | | LC50 fish | 2-5 mg/l |
| | | EC50 daphnia | 3-10 mg/l |

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number



8 / 10

CRC Industries UK Limited
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : POLYMER REMOVER
Ref.Nr.: BDS000021_3_20171011 (EN) **Creationdate :** 11.10.17 Version : 3.1
Replaces: BDS000021_20170629

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information



9 / 10

CRC Industries UK Limited
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

| | |
|---|--|
| Productname : POLYMER REMOVER | Creationdate : 11.10.17 Version : 3.1 |
| Ref.Nr.: BDS000021_3_20171011 (EN) | Replaces: BDS000021_20170629 |

*Explanation hazard statements: H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H301 : Toxic if swallowed.
H304 : May be fatal if swallowed and enters airways.
H311 : Toxic in contact with skin.
H319 : Causes serious eye irritation.
H331 : Toxic if inhaled.
H336 : May cause drowsiness or dizziness.
H370 : Causes damage to organs .
H411 : Toxic to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.