

**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**SP 350 II**  
Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

### 1.3. Details of the supplier of the safety data sheet

**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele  
Belgium  
Tel.: +32(0)52/45.60.11  
Fax.: +32(0)52/45.00.34  
E-mail : hse@crcind.com

| Subsidiaries                    |                                                                         | Tel               | Fax              |
|---------------------------------|-------------------------------------------------------------------------|-------------------|------------------|
| CRC Industries Finland Oy       | Laurinkatu 57 A 23 B, 08100 Lohja                                       | +358/(19)32.921   | +358/(19)383.676 |
| CRC Industries France           | 6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex                 | 01.34.11.20.00    | 01.34.11.09.96   |
| CRC Industries Deutschland GmbH | Südring 9, D-76473 Iffezheim                                            | (07229) 303.0     | (07229)30 32 66  |
| CRC INDUSTRIES IBERIA S.L.U.    | GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA | 0034/921.427.546  | 0034/921.436.270 |
| CRC Industries Sweden           | Kryptongatan 14, 431 53 Mölndal                                         | 0046/31 706 84 80 | 0046/31 27 39 91 |

### 1.4. Emergency telephone number

**CRC Industries Europe, Belgium:** Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosols, category 1  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.

**Health:** Skin irritation, category 2



|                      |                      |                       |                        |
|----------------------|----------------------|-----------------------|------------------------|
| <b>Productname :</b> | SP 350 II            | <b>Creationdate :</b> | 18.07.13 Version : 2.0 |
| <b>Ref.Nr.:</b>      | BDS000567_3_20130718 | <b>Replaces:</b>      | BDS000567_20111004     |

|                        |                                                                                                                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | Causes skin irritation.<br>Eye irritation, category 2<br>Causes serious eye irritation.<br>Specific target organ toxicity - single exposure, category 3<br>May cause drowsiness or dizziness. |
| <b>Environment:</b>    | Hazardous to the aquatic environment, chronic category 2<br>Toxic to aquatic life with long lasting effects.                                                                                  |
| <b>Other hazards :</b> | None                                                                                                                                                                                          |

#### Classification according to 67/548/EEC or 1999/45/EC:

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| <b>Health:</b>      | R38: Irritating to skin.<br>R67: Vapours may cause drowsiness and dizziness.                        |
| <b>Physical:</b>    | EXTREMELY FLAMMABLE                                                                                 |
| <b>Environment:</b> | R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product identifier:</b>              | Contains:<br>hydrocarbons                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Hazard pictogram(s):</b>             |                                                                                                                                                                                                                                                                                                          |
| <b>Signal word:</b>                     | Danger                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Hazard statement(s):</b>             | H222 : Extremely flammable aerosol.<br>H229 : Pressurised container: May burst if heated.<br>H315 : Causes skin irritation.<br>H319 : Causes serious eye irritation.<br>H336 : May cause drowsiness or dizziness.<br>H411 : Toxic to aquatic life with long lasting effects.                                                                                                                                                                                                                                                                                        |
| <b>Precautionary statement(s):</b>      | P102 : Keep out of reach of children.<br>P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 : Do not spray on an open flame or other ignition source.<br>P251 : Do not pierce or burn, even after use.<br>P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.<br>P271 : Use only outdoors or in a well-ventilated area.<br>P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.<br>P501-2 : Dispose of contents/container to an authorised waste collection point. |
| <b>Supplemental Hazard information:</b> | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

#### 2.3. Other hazards

None

**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

| Hazardous ingredient                                                | CAS-nr.    | EC-nr     | w/w % | symbol | R-phrases*        | Notes |
|---------------------------------------------------------------------|------------|-----------|-------|--------|-------------------|-------|
| Naphtha (petroleum), hydrotreated light                             | 64742-49-0 | 921-024-6 | 10-25 | F,Xn,N | 11-38-51/53-65-67 | B     |
| Naphtha (petroleum), hydrodesulfurized light (benzene<0.1%)         | 92045-53-9 | 927-510-4 | 10-25 | F,Xn,N | 11-38-51/53-65-67 | B     |
| mineral oil (IP 346 DMSO extract < 3%)                              | -          | -         | 10-25 | -      | -                 | B     |
| 3-butoxypropan-2-ol; propylene glycol monobutyl ether               | 5131-66-8  | 225-878-4 | 5-10  | Xi     | 36/38             |       |
| Distillates (petroleum), hydrotreated light; Kerosine - unspecified | 64742-47-8 | 265-149-8 | 5-10  | Xn     | 10-65-66-67       | B     |
| carbon dioxide                                                      | 124-38-9   | 204-696-9 | 1-5   | -      | -                 | A,G   |
| sulfonic acids,petroleum,sodium salts                               | 68608-26-4 | 271-781-5 | 1-5   | Xi     | 36                |       |

#### Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

| Hazardous ingredient                                                | Registration number | CAS-nr.    | EC-nr     | w/w % | Hazard Class and Category                                              | Hazard statement         | Notes |
|---------------------------------------------------------------------|---------------------|------------|-----------|-------|------------------------------------------------------------------------|--------------------------|-------|
| Naphtha (petroleum), hydrotreated light                             | 01-2119475514-35    | 64742-49-0 | 921-024-6 | 10-25 | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H225,H315,H336,H304,H411 | B     |
| Naphtha (petroleum), hydrodesulfurized light (benzene<0.1%)         | 01-2119475515-33    | 92045-53-9 | 927-510-4 | 10-25 | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H225,H315,H336,H304,H411 | B     |
| mineral oil (IP 346 DMSO extract < 3%)                              |                     | -          | -         | 10-25 | -                                                                      | -                        | B     |
| 3-butoxypropan-2-ol; propylene glycol monobutyl ether               | 01-2119475527-28    | 5131-66-8  | 225-878-4 | 5-10  | Eye Irrit. 2, Skin Irrit. 2                                            | H319,H315                |       |
| Distillates (petroleum), hydrotreated light; Kerosine - unspecified |                     | 64742-47-8 | 265-149-8 | 5-10  | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1                                   | H226,H336,H304           | B     |
| carbon dioxide                                                      |                     | 124-38-9   | 204-696-9 | 1-5   | Press. Gas                                                             | H280                     | A,G   |

#### Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Contact with eyes :**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact



**CRC Industries Europe bvba**

Touwslagerstraat 1, 9240 Zele – Belgium

Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

|                            |                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                            | lenses, if present and easy to do. Continue rinsing.<br>If eye irritation persists: Get medical advice/attention.                                                    |
| <b>Contact with skin :</b> | Take off contaminated clothing and wash before reuse.<br>IF ON SKIN: Wash with plenty of soap and water.<br>If skin irritation occurs: Get medical advice/attention. |
| <b>Inhalation :</b>        | IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>Call a POISON CENTER or doctor/physician if you feel unwell.                           |
| <b>Ingestion :</b>         | If swallowed do not induce vomiting because of risk of aspiration into the lungs.<br>If aspiration is suspected obtain immediate medical attention                   |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                       |                                                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation :</b>   | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness                                                                                 |
| <b>Ingestion :</b>    | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.<br>Symptoms : sore throat, abdominal pain, nausea, vomiting |
| <b>Skin contact :</b> | Irritating to skin<br>Symptoms : redness and pain                                                                                                                        |
| <b>Eye contact :</b>  | Irritating to eyes<br>Symptoms : redness and pain, impaired vision                                                                                                       |

#### 4.3. Indication of any immediate medical attention and special treatment needed

|                         |                                                                                                                     |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>General Advice :</b> | If you feel unwell, seek medical advice (show the label where possible)<br>If symptoms persist always call a doctor |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO, CO<sub>2</sub>

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources



**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

## 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses  
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

## 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material  
Place in appropriate container  
This material and/or its container must be disposed of as hazardous waste.

## 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.  
Eyewash bottles should be available

## 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Keep out of reach of children.

## 7.3. Specific end use(s)

Anti Corrosion Products

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Exposure limits :



**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

| Hazardous ingredient                                        | CAS-nr.  | method         |
|-------------------------------------------------------------|----------|----------------|
| <b>EU established exposure limits:</b>                      |          |                |
| carbon dioxide                                              | 124-38-9 | TWA 5000 ppm   |
| <b>National established exposure limits, United Kingdom</b> |          |                |
| carbon dioxide                                              | 124-38-9 | TWA 5000 ppm   |
|                                                             |          | STEL 15000 ppm |

## 8.2. Exposure controls

|                                  |                                                                                                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Control procedures :</b>      | Ensure adequate ventilation<br>Keep away from heat and sources of ignition<br>Take precautionary measures against static discharges                            |
| <b>Personal protection :</b>     | Take precautions to avoid contact with skin and eyes when handling the product.<br>Ensure adequate ventilation                                                 |
| <b>inhalation :</b>              | In case of insufficient ventilation, wear suitable respiratory equipment.<br>Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX) |
| <b>hands and skin :</b>          | Wear suitable protective gloves against chemicals<br>(nitrile)                                                                                                 |
| <b>eyes :</b>                    | Wear safety goggles.                                                                                                                                           |
| <b>Environmental protection:</b> | Avoid release to the environment.<br>Collect spillage.                                                                                                         |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

|                                         |                                  |
|-----------------------------------------|----------------------------------|
| <b>Apperance : physical state :</b>     | CO2 propelled liquid.            |
| <b>colour :</b>                         | Off-white.                       |
| <b>odour :</b>                          | Characteristic odor.             |
| <b>pH :</b>                             | Not applicable.                  |
| <b>Boiling point/range :</b>            | 60-250 °C                        |
| <b>Flash point :</b>                    | < 0 °C                           |
| <b>Evaporation rate :</b>               | Not applicable.                  |
| <b>Explosion limits : upper limit :</b> | Not available.                   |
| <b>lower limit :</b>                    | Not available.                   |
| <b>Vapour pressure :</b>                | Not available.                   |
| <b>Relative density :</b>               | 0.82 g/cm <sup>3</sup> (@ 20°C). |
| <b>Solubility in water :</b>            | Emulsifies with water            |
| <b>Auto-ignition :</b>                  | > 200 °C                         |
| <b>Viscosity :</b>                      | 8.4 mPa.s (@ 20°C).              |

### 9.2. Other information

**VOC:** 360 g/l

## SECTION 10: Stability and reactivity



**CRC Industries Europe bvba**

Touwslagerstraat 1, 9240 Zele – Belgium

Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – [www.crcind.com](http://www.crcind.com)

**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO<sub>2</sub>

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                       |                                                                                                              |
|-----------------------|--------------------------------------------------------------------------------------------------------------|
| <b>Inhalation :</b>   | Inhalation of solvent vapours may give rise to nausea, headaches and dizziness                               |
| <b>Ingestion :</b>    | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. |
| <b>Skin contact :</b> | Irritating to skin                                                                                           |
| <b>Eye contact :</b>  | Irritating to eyes                                                                                           |

### Toxicological data :

| Hazardous ingredient                                                | CAS-nr.    | method          |               |
|---------------------------------------------------------------------|------------|-----------------|---------------|
| 3-butoxypropan-2-ol; propylene glycol monobutyl ether               | 5131-66-8  | LD50 oral rat   | 2700 mg/kg    |
|                                                                     |            | LC50 inhal.rat  | 651 mg/l      |
|                                                                     |            | LD50 derm.rat   | 2000 mg/kg    |
| Distillates (petroleum), hydrotreated light; Kerosine - unspecified | 64742-47-8 | LD50 oral rat   | > 2000 mg/kg  |
|                                                                     |            | LD50 derm.rabit | > 2000 mg/kg  |
| Naphtha (petroleum), hydrotreated light                             | 64742-49-0 | LD50 oral rat   | > 5000 mg/kg  |
|                                                                     |            | LC50 inhal.rat  | > 25000 mg/m3 |
|                                                                     |            | LD50 derm.rat   | > 2000 mg/kg  |
| Naphtha (petroleum), hydrodesulfurized light (benzene<0.1%)         | 92045-53-9 | LD50 oral rat   | > 5000 mg/kg  |



**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

|  |  |                |              |
|--|--|----------------|--------------|
|  |  | LC50 inhal.rat | > 20 mg/l    |
|  |  | LD50 derm.rat  | > 2000 mg/kg |

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2  
Toxic to aquatic life with long lasting effects.

#### Ecotoxicological data:

| Hazardous ingredient                                        | CAS-nr.    | method       |               |
|-------------------------------------------------------------|------------|--------------|---------------|
| 3-butoxypropan-2-ol; propylene glycol monobutyl ether       | 5131-66-8  | LC50 fish    | 560-1000 mg/l |
|                                                             |            | EC50 daphnia | > 1000 mg/l   |
| Naphtha (petroleum), hydrotreated light                     | 64742-49-0 | LC50 fish    | > 10 mg/l     |
|                                                             |            | EC50 daphnia | 3 mg/l        |
| Naphtha (petroleum), hydrodesulfurized light (benzene<0.1%) | 92045-53-9 | IC50 algae   | 10-30 mg/l    |
|                                                             |            | LC50 fish    | > 10 mg/l     |
|                                                             |            | EC50 daphnia | 3 mg/l        |

### 12.2. Persistence and degradability

No experimental data available

### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :**

This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.





**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

**National regulations :** Disposal should be in accordance with local, state or national legislation

## SECTION 14: Transport information

### 14.1. UN number

UN-number : 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS (naphta's)

### 14.3. Transport hazard class(es)

Class: 2.1  
ADR/RID - Classification code: 5F

### 14.4. Packing group

Packing group: Not applicable.

### 14.5. Environmental hazards

ADR/RID - Environmentally  
hazardous: Yes  
IMDG - Marine pollutant: Marine pollutant  
IATA/ICAO - Environmentally  
hazardous: Yes

### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D, S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.  
Regulation (EC) No 1907/2006 (REACH)  
EU-directive 99/45/EC



**Productname :** SP 350 II  
**Ref.Nr.:** BDS000567\_3\_20130718

**Creationdate :** 18.07.13 Version : 2.0  
**Replaces:** BDS000567\_20111004

Regulation (EC) No 1272/2008 (CLP)

## 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation risk-phrases:

- R10: Flammable.
- R11: Highly flammable.
- R36: Irritating to eyes.
- R38: Irritating to skin.
- R65: Harmful: may cause lung damage if swallowed.
- R66: Repeated exposure may cause skin dryness or cracking.
- R67: Vapours may cause drowsiness and dizziness.
- R36/38: Irritating to eyes and skin.
- R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

\*Explanation hazard statements: - : -

- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H280 : Contains gas under pressure; may explode if heated.
- H304 : May be fatal if swallowed and enters airways.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.
- H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : 2.2. Label elements

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.