

Productname : Striping Paint Long Life      Creationdate : 29.06.17 Version : 3.0  
 Ref.Nr.: BDS001383\_3\_20170629 (EN)      Replaces: BDS001383\_20150327

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Striping Paint Long Life**  
Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints

### 1.3. Details of the supplier of the safety data sheet

**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele  
Belgium  
Tel.: +32(0)52/45.60.11  
Fax.: +32(0)52/45.00.34  
E-mail : hse@crcind.com

| Subsidiaries                    |   | Tel               | Fax              |
|---------------------------------|---|-------------------|------------------|
| CRC Industries Finland Oy       | Laurinkatu 57 A 23 B, 08100 Lohja                                       | +358/(19)32.921   |                  |
| CRC Industries France           | 6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex                 | 01.34.11.20.00    | 01.34.11.09.96   |
| CRC Industries Deutschland GmbH | Südring 9, D-76473 Iffezheim  | (07229) 303 0     | (07229)30 32 66  |
| CRC INDUSTRIES IBERIA S.L.U.    | GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA | 0034/921.427.546  | 0034/921.436.270 |
| CRC Industries Sweden           | Laxfiskevägen 16, 433 38 Partille                                       | 0046/31 706 84 80 | 0046/31 27 39 91 |

### 1.4. Emergency telephone number

**CRC Industries Europe, Belgium:** Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosols, category 1  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.

Classification is based on test data.



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)  
**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

**Health:** Not classified  
 Classification based on calculation method.  
**Environment:** Not classified  
 Classification based on calculation method.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

#### Hazard pictogram(s):



**Signal word:** Danger  
**Hazard statement(s):** H222 : Extremely flammable aerosol.  
 H229 : Pressurised container: May burst if heated.  
**Precautionary statement(s):** P102 : Keep out of reach of children.  
 P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 : Do not spray on an open flame or other ignition source.  
 P251 : Do not pierce or burn, even after use.  
 P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

## 2.3. Other hazards

No information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

| Hazardous ingredient  | Registration number | CAS-nr.    | EC-nr     | w/w %  | Hazard Class and Category             | Hazard statement | Notes |
|---|---------------------|------------|-----------|--------|---------------------------------------|------------------|-------|
| dimethyl ether  | 01-2119472128-37    | 115-10-6   | 204-065-8 | 50-100 | Flam. Gas 1, Press. Gas               | H220,H280        | A     |
| Naphtha (petroleum), hydrotreated light   | 01-2119475133-43    | 64742-49-0 | 265-151-9 | 10-25  | Asp. Tox. 1                           | H304             | B,P   |
| n-butyl acetate   | 01-2119485493-29    | 123-86-4   | 204-658-1 | <10    | Flam. Liq. 3, STOT SE 3               | H226,H336        |       |
| ethyl acetate   | 01-2119475103-46    | 141-78-6   | 205-500-4 | <10    | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 | H225,H319,H336   | B     |
| <b>Explanation notes</b>  |                     |            |           |        |                                       |                  |       |
| A : substance with Community workplace exposure limit                               |                     |            |           |        |                                       |                  |       |
| B : substance with national established workplace exposure limit                    |                     |            |           |        |                                       |                  |       |
| P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7) |                     |            |           |        |                                       |                  |       |

**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                            |  |
|----------------------------|--|
| <b>Contact with eyes :</b> | If substance has got into eyes, immediately wash out with plenty of water<br>If eye irritation persists: Get medical advice/attention.             |
| <b>Contact with skin :</b> | Wash with plenty of soap and water.<br>If skin irritation occurs: Get medical advice/attention.  |
| <b>Inhalation :</b>        | IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>Call a POISON CENTER or doctor/physician if you feel unwell.         |
| <b>Ingestion :</b>         | If swallowed do not induce vomiting because of risk of aspiration into the lungs.<br>If aspiration is suspected obtain immediate medical attention |

### 4.2. Most important symptoms and effects, both acute and delayed

|                       |  |
|-----------------------|--|
| <b>Inhalation :</b>   | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness   |
| <b>Ingestion :</b>    | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.<br>Symptoms : sore throat, abdominal pain, nausea, vomiting |
| <b>Skin contact :</b> | May cause irritation.<br>Symptoms : redness and pain   |
| <b>Eye contact :</b>  | May cause irritation.<br>Symptoms : redness and pain   |

### 4.3. Indication of any immediate medical attention and special treatment needed

|                         |   |
|-------------------------|---|
| <b>General Advice :</b> | If you feel unwell, seek medical advice (show the label where possible)<br>If symptoms persist always call a doctor |
|-------------------------|---|

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

foam, carbon dioxide or dry agent  
Do not use water jet extinguishing media, due to the risk of spreading fire.

### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses  
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

### 6.4. Reference to other sections

For further information see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Keep out of reach of children.

### 7.3. Specific end use(s)

Paints

## SECTION 8: Exposure controls/personal protection



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)  
**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

## 8.1. Control parameters

### Exposure limits :

| Hazardous ingredient  | CAS-nr.  | method |          |
|---|----------|--------|----------|
| <b>EU established exposure limits:</b>                      |          |        |          |
| dimethyl ether  | 115-10-6 | TWA    | 1000 ppm |
| ethyl acetate   | 141-78-6 | TWA    | 200 ppm  |
|   |          | STEL   | 400 ppm  |
| <b>National established exposure limits, United Kingdom</b> |          |        |          |
| dimethyl ether  | 115-10-6 | TWA    | 400 ppm  |
|   |          | STEL   | 500 ppm  |
| n-butyl acetate   | 123-86-4 | TWA    | 150 ppm  |
|   |          | STEL   | 200 ppm  |
| ethyl acetate   | 141-78-6 | TWA    | 200 ppm  |
|   |          | STEL   | 400 ppm  |

## 8.2. Exposure controls

|                                     |  |
|-------------------------------------|--|
| <b>Control procedures :</b>         | Ensure adequate ventilation<br>Keep away from heat and sources of ignition<br>Take precautionary measures against static discharges  |
| <b>Personal protection :</b>        | Take precautions to avoid contact with skin and eyes when handling the product.<br>It is good practice to wear gloves and to provide adequate ventilation whenever using the product.<br>In all cases handle and use the product in accordance with good industrial hygiene practices. |
| <b>inhalation :</b>                 | In case of insufficient ventilation, wear suitable respiratory equipment.  |
| recommended respiratory protection: | Air purifying respirator equipped with organic gas/vapor cartridge (type AX)   |
| <b>hands and skin :</b>             | Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time.  |
| Recommended gloves:                 | (polyvinylalcohol)   |
| <b>eyes :</b>                       | Wear safety eyewear according to EN 166.   |
| <b>Environmental protection:</b>    | Avoid release to the environment.<br>Collect spillage.   |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

|                                     |                       |
|-------------------------------------|-----------------------|
| <b>Apperance : physical state :</b> | DME propelled liquid. |
| <b>colour :</b>                     | See color cap.        |
| <b>odour :</b>                      | Characteristic odor.  |
| <b>pH :</b>                         | Not applicable.       |
| <b>Boiling point/range :</b>        | 35 °C                 |



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

**Flash point :** < 0 °C  
**Evaporation rate :** Not available.  
**Explosion limits : upper limit :** Not available.  
**lower limit :** Not available.  
**Vapour pressure :** < 110 kPa (@ 20°C).  
**Relative density :** 1.0 g/cm<sup>3</sup> (@ 20°C).  
**Solubility in water :** Insoluble in water  
**Auto-ignition :** > 200 °C  
**Viscosity :** Not available.

## 9.2. Other information

# SECTION 10: Stability and reactivity

## 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

## 10.2. Chemical stability

Stable

## 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

## 10.4. Conditions to avoid

Avoid overheating

## 10.5. Incompatible materials

Strong oxidising agent

## 10.6. Hazardous decomposition products

CO,CO<sub>2</sub>

# SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

**acute toxicity:** based on available data the classification criteria are not met  
**skin corrosion/irritation:** based on available data the classification criteria are not met  
**serious eye damage/irritation:** based on available data the classification criteria are not met  
**respiratory or skin sensitisation:** based on available data the classification criteria are not met  
**germ cell mutagenicity:** based on available data the classification criteria are not met



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)  
**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

**carcinogenicity:** based on available data the classification criteria are not met  
**toxicity for reproduction:** based on available data the classification criteria are not met  
**STOT-single exposure:** based on available data the classification criteria are not met  
**STOT repeated exposure:** based on available data the classification criteria are not met  
**aspiration hazard:** based on available data the classification criteria are not met

#### Information on likely routes of exposure:

**Inhalation :** Inhalation of solvent vapours may give rise to nausea, headaches and dizziness  
**Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.  
**Skin contact :** Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis  
**Eye contact :** Repeated exposure may cause skin dryness or cracking. May cause irritation.

#### Toxicological data :

| Hazardous ingredient | CAS-nr.  | method          |               |
|----------------------|----------|-----------------|---------------|
| dimethyl ether       | 115-10-6 | LC50 inhal.rat  | 309 mg/l      |
| n-butyl acetate      | 123-86-4 | LD50 oral rat   | 10760 mg/kg   |
|                      |          | LC50 inhal.rat  | > 20 mg/l     |
| ethyl acetate        | 141-78-6 | LD50 derm.rabit | > 1400 mg/kg  |
|                      |          | LD50 oral rat   | 5620 mg/kg    |
|                      |          | LC50 inhal.rat  | 30 mg/l       |
|                      |          | LD50 derm.rabit | > 20000 mg/kg |

## SECTION 12: Ecological information

### 12.1. Toxicity

Not classified

#### Ecotoxicological data:

| Hazardous ingredient | CAS-nr.  | method       |            |
|----------------------|----------|--------------|------------|
| dimethyl ether       | 115-10-6 | IC50 algae   | 154.9 mg/l |
|                      |          | LC50 fish    | 4.1 mg/l   |
|                      |          | EC50 daphnia | 4.4 mg/l   |
| n-butyl acetate      | 123-86-4 | IC50 algae   | 647 mg/l   |
|                      |          | LC50 fish    | 18 mg/l    |
|                      |          | EC50 daphnia | 44 mg/l    |
| ethyl acetate        | 141-78-6 | IC50 algae   | 5600 mg/l  |
|                      |          | LC50 fish    | 230 mg/l   |
|                      |          | EC50 daphnia | 610 mg/l   |



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

### 12.2. Persistence and degradability

No information available

### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

No information available

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No experimental data available  
GWP (global warming potential): 1

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations :** Disposal should be in accordance with local, state or national legislation

## SECTION 14: Transport information

### 14.1. UN number

UN-number : 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Class: 2.1  
ADR/RID - Classification code: 5F

### 14.4. Packing group

Packing group: Not applicable.



**Productname :** Striping Paint Long Life  
**Ref.Nr.:** BDS001383\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 3.0  
**Replaces:** BDS001383\_20150327

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

#### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D, S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Regulation (EC) No 1907/2006 (REACH)  
Regulation (EC) No 1272/2008 (CLP)  
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

#### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation hazard statements: H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

REVISIONS IN CHAPTRE : 8.2. Exposure controls  
acronyms and synonyms: TWA = time weight average  
STEL = short time exposure limit  
VOC = volatile organic compounds  
PBT = persistant bioaccumulative toxic  
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in



---

|                      |                           |                       |                        |
|----------------------|---------------------------|-----------------------|------------------------|
| <b>Productname :</b> | Striping Paint Long Life  | <b>Creationdate :</b> | 29.06.17 Version : 3.0 |
| <b>Ref.Nr.:</b>      | BDS001383_3_20170629 (EN) | <b>Replaces:</b>      | BDS001383_20150327     |

---

conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

