

## Acryl RAL

### 1. General description

Top coat based on acrylic resin to achieve high gloss and good characteristics against weather influences.

### 2. Features

- Very fast drying.
- Unique combination of flexibility and hardness providing an excellent adherence to the metal surface.
- Suitable for use on a wide variety of hard surfaces throughout industries.
- High UV resistance.
- Does not contain heavy metals.
- Good covering ability.
- Preserves its shine and intensive colour for a long time.

### 3. Applications

• Acryl Ral is recommended as a protecting paint for all kind of repair of lacquered surfaces. Acryl Ral is also used as a high quality paint for a wide variety of applications.

### 4. Directions

- Shake well before use.
- Shake until the agitator ball moves freely in the can.
- Apply to a clean, dry surface.
- Apply a thin even film.
- Best results are obtained with 2 lighter rather than 1 heavy coat. Additional coats can be applied after 3 - 5 minutes (max 30 min).
- Do not use on energized equipment.
- Do not use on sensitive electronic equipment.
- Clean the aerosol valve by turning the can upside down and spraying until only propellant escapes.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

### 5. Typical product data (without propellant)

Appearance

Not available.

Density

0.775 g/cm<sup>3</sup> (@ 20°C).

Color

See color cap.

Flash Point

< 0 °C

Drying time active product

Not available.

Adhesion on steel dry coating

Not available.

### Remarks



# Technical Data Sheet

---

## Acryl RAL

---

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

**Version** CRC\_GREEN-ACRYL\_RAL-20181206  
**Date** 06/12/2018

