



1. General description

Сухая, нежирная смазка поверхности.



2. Features

- Clean, dry and non-oily.
- Functional over a wide temperature range.
- Contains PTFE for extra lubricity.
- Produces a very low coefficient of friction.
- Most effective when low speeds and light loads are involved.
- Устойчивость к высоким температурам.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.

3. Applications

- Coin mechanisms.
- Plastic drives and sliding mechanisms.
- Fine mechanics.
- Pneumatic tools.
- Precision instruments.
- Valves.
- Surface treatment.



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





- Release agent for moulding plastic and rubber.
- Transfer of CRC Dry Lube to moulded parts is negligible, minimizing interference with post finishing operations.

4. Directions

- Shake well before use.
- Хорошо встряхивайте до тех пор, пока смесительный шарик не начнет свободно перемещаться внутри аэрозольного баллона.
- To remove residues or excess product, use one of the CRC cleaners.
- Spray from a distance of approximately 20 - 30 cm.
- Allow to dry at room temperature.
- Do not use on energized equipment.
- Листы безопасности (MSDS) согласно Ст.31 Положения ЕС N° 1907/2006 Ст.3 со всеми приложениями доступны для всех продуктов CRC.

5. Typical product data (without propellant)

Внешний вид	Жидкость.
Цвет	беловатый.
Запах	Растворитель.
Плотность	0.75 g/cm ³ (@ 20°C).
Точка вспышки	< 0 °C
Density active product	2.16 g/cm ³ (@ 20°C).
Operating temperature active product	max 250 °C
Время высыхания активного продукта	15 min

6. Packaging


Аэрозоль	12x400 ML	Ref. : 30519
	12x500 ML	Ref. : 30520

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





Technical data sheet
Dry Lube

Reference : 10255

Версия CRC_GREEN-DRY_LUBE-20131003
Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

