

1. General description



2. Features

- Excellent touch-up for galvanised surfaces.
- Long term corrosion protection.
- Totally free of lead and chromates.
- None chlorinated solvents.
- Unique combination of flexibility and hardness providing an excellent adherence to the metal surface.

3. Applications

- Cleaning mechanical parts.
- Handling equipment.
- Chains.
- Railroad equipment.
- Agricultural equipment.
- Long term outdoor corrosion protection.
- Corrosion protection of all ferrous materials.
- Touch-up of galvanised equipment after repair.
- Touch-up of parts after hot dip galvanising.



- Pylons (telecom, power transfer,...)
- Silencers on combustion engines.

4. Directions

- Shake well before use.
- Shake until the agitator ball moves freely in the can.
- Apply to a clean, dry surface.
- Apply a thin even film.
- Best results are obtained with 2 lighter rather than 1 heavy coat. Additional coats can be applied after 15 - 20 minutes.
- Do not use on energized equipment.
- Do not use on sensitive electronic equipment.
- Clean the aerosol valve by turning the can upside down and spraying until only propellant escapes.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Appearance	Likwidu.
Kulur	Griz.
Riħa	Solvent.
Density	0.969 g/cm ³ (@ 20°C).
Flash Point	< 0 °C
Drying time active product	240 min
Typical coat weight	30 - 40 µm
Flexibility of dry coating	OK 6 mm mandrel
Adhesion on steel dry coating	0/1 GT
salt spray resistance active product	100 h
Operating temperature active product	-30 till +200 °C


6. Packaging

ajrusol	12x400 ML	Ref. : 10250
	12x500 ML	Ref. : 30423



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-GALVA_BRITE-20150717

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

