



1. General description

Visoko učinkovito čistilo in odmaščevalec za mehansko opremo. Odmaščuje in odstranjuje olje, mast, vosek, umazanijo in druge onesnaževalce, ki povzročajo nepravilno delovanje. Hitro sušenje za hiter odziv in zmanjšanje izpada opreme. Ne pušča sledi.



2. Features

- Attacks encrusted residues. Quickly penetrates and cuts through dirt.
- Does not leave a residue.
- Non corrosive.
- Fast evaporation to minimize downtime.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Cleaning mechanical parts.
- Pneumatic tools.
- Compressors.



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

1/1





- Handling equipment.
- Open drive mechanisms.
- Wire ropes.
- Chains.
- Bearings.

4. Directions

- Spray liberally and allow to run off.
- Use extension tube for more precise application.
- Use only with adequate ventilation.
- Test before use on sensitive materials.
- Do not use on sensitive electronic equipment.
- Do not use on energized equipment.
- Allow to dry completely before reactivation.
- Allow to dry at room temperature.
- Repeat if necessary.
- Protect and re-lubricate if necessary.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

	Aerosol	Razsuto stanje
NSF registration	111201 cat. A8, K1	132248 cat. A8, K1
Appearance	Tekočina.	Tekočina.
Barva	Brez barve.	Brez barve.
Vonj	Sladko podobnu etru.	Sladko podobnu etru.
Density	0.81 g/cm ³ (@ 20°C).	0.81 g/cm ³ (@ 20°C).
Gostota hlapov	4 (@ 20°C).	4 (@ 20°C).
Flash Point	25 °C (zaprta posoda)	25 °C (zaprta posoda)
Temperatura samodejnega vžiga	> 200 °C	> 200 °C
Stopnja hlapenja	19 (Eter=1)	19 (Eter=1)
Viskoznost	0.76 mPa.s (@ 20°C).	0.76 mPa.s (@ 20°C).
Surface tension active product	23 mN/m	23 mN/m





Kauri Butanol value active product >150 > 150

6. Packaging

Aerosol	12x500 ML	Ref. : 10321
Razsuto stanje	20 L	Ref. : 10326
	200 L	Ref. : 30452
	2x5 L	Ref. : 10325

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-INDUSTRIAL_DEGREASER-20131003

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

