



## 1. General description



## 2. Features

- Forms a colourless, non-hardening film, eliminating squeaking, binding and sticking.
- Protects metals and alloys.
- Penetrates quickly.
- Protects plastics and rubbers.
- Displaces and seals out water and moisture.
- Functional over a wide temperature range.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

## 3. Applications

- Coin mechanisms.
- Plastic drives and sliding mechanisms.
- Fine mechanics.



- Pneumatic tools.
- Precision instruments.
- Valves.
- Anti-freeze for rubbers.
- Assembly of packings.
- Protection and maintenance of rubbers.
- Release agent for moulding plastic and rubber.

#### 4. Directions

- Apply a thin even film.
- Use extension tube for more precise application.
- Repeat if necessary.
- Do not use on energized equipment.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

#### 5. Typical product data (without propellant)

Appearance	ajrusol	Massa
Kulur	Likwidu.	Likwidu.
Riha	Bla kulur.	Bla kulur.
Density	Solvent.	Solvent.
Flash Point	0.72 g/cm <sup>3</sup> (@ 20°C).	0.72 g/cm <sup>3</sup> (@ 20°C).
Temperatura tat-tqabbid minnu nnifsu	- 26 °C (Tazza Magħluqa)	- 26 °C (Tazza Magħluqa)
Densità tal-fwar	> 200 °C	> 200 °C
Flash point active product	>3 (@ 20°C).	>3 (@ 20°C).
Operating temperature active product	>300 °C (Tazza Magħluqa)	> 300 °C (Tazza Magħluqa)
Surface tension active product	-40 till 200 °C	-40 --> 200 °C
Dielectric strenght active product	21 mN/m	21 mN/m
Dynamic viscosity active product	35 kV	35 kV
	10.000 - 12.000 mPa.s (@ 20°C).	10.000 - 12.000 mPa.s (@ 20°C).


#### 6. Packaging

ajrusol	12x500 ML	Ref. : 32635
---------	-----------	--------------



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





Massa

2x5 L

Ref. : 30053

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC\_GREEN-INDUSTRIAL\_SILICONE-20170725

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

