

## 1. General description

Керамическая смазка для сборки, действует от  $-40^{\circ}\text{C}$  до  $+1400^{\circ}\text{C}$ . Предотвращает заедание и фреттинг-коррозию всех металлических резьбовых соединений. Защищает тормозные детали от прокаливания, предотвращает шум дисковых тормозов. Подходит для ABS. Не является потенциалом для гальванической коррозии.



## 2. Features

- Enables easy disassembly of threaded parts, gaskets and flanges, even after a long time of to high pressure and high temperature.
- Protects against burning-in, corrosion and seizing.
- Stops and prevents disc brake noise and vibration.
- None chlorinated solvents.
- Totally free of lead and chromates.
- Excellent water resistance.
- Functional over a wide temperature range.

## 3. Applications

- Sound deadening mass for squeaking brakes.
- Flange connections under high temperature conditions.
- Pin or spline connections.
- Резьбовые соединения.

## 4. Directions



- Apply to a clean, dry surface.
- Наносите тонким ровным слоем.
- Do not mix with other products.
- Do not use on energized equipment.
- Use only with adequate ventilation.
- To remove residues or excess product, use one of the CRC cleaners.
- Листы безопасности (MSDS) согласно Ст.31 Положения ЕС N° 1907/2006 Ст.3 со всеми приложениями доступны для всех продуктов CRC.

### 5. Typical product data (without propellant)


Внешний вид	Аэрозоль паста.	Большого объема Паста.
Цвет	беловатый.	белый.
Запах	Растворитель.	Ощутимый запах.
Точка вспышки	< 0 °C (закрытый тигель)	>200 °C
Плотность	0.857 g/cm <sup>3</sup> (@ 20°C).	1.419 g/cm <sup>3</sup> (@ 20°C).
Flash point active product	>200 °C (открытый тигель)	>200 °C (открытый тигель)
Density active product	1,419 g/cm <sup>3</sup> (@ 20°C).	1,419 g/cm <sup>3</sup> (@ 20°C).
Operating temperature active product	-40 -->+1400 °C	-40-->+1400 °C
4-ball weld load active product	3800 N	3800 N
NLGI class	3	3

### 6. Packaging

Аэрозоль	12x300 ML	Ref. : 10723
	12x500 ML	Ref. : 30108
Большого объема	1 KG	Ref. : 20706
TI	can 12x500 G	Ref. : 32344
TU	12x100 G	Ref. : 10720

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that





Technical data sheet  
**Metal Free Paste**

Reference : 10434

---

you register on our website for this product, thus enabling you to automatically receive any future updates.

Версия CRC\_GREEN-METAL\_FREE\_PASTE-20131003

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**[www.crcind.com](http://www.crcind.com)**

