

1. General description

Keramična sestavljena pasta,
od -40°C do +1400°C.
Preprečuje prijemanje in
izrezljanje vseh kovinskih
vdelanih delov. Zaščiti
lomljive dele pred gorenjem in
prepreči glasen zlom diska.
Primerna za ABS. Nobene
možnosti za galvansko
korozijo.




2. Features

- Enables easy disassembly of threaded parts, gaskets and flanges, even after a long time of to high pressure and high temperature.
- Protects against burning-in, corrosion and seizing.
- Stops and prevents disc brake noise and vibration.
- None chlorinated solvents.
- Totally free of lead and chromates.
- Excellent water resistance.
- Functional over a wide temperature range.

3. Applications

- Sound deadening mass for squeaking brakes.
- Flange connections under high temperature conditions.
- Pin or spline connections.
- Threaded connections.

4. Directions



- Apply to a clean, dry surface.
- Apply a thin even film.
- Do not mix with other products.
- Do not use on energized equipment.
- Use only with adequate ventilation.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

	Aerosol	Razsuto stanje
Appearance	Pasta.	Pasta.
Barva	Sivkasto belo.	Belo.
Vonj	Topilo.	Zaznaven vonj.
Flash Point	< 0 °C (zaprta posoda)	>200 °C
Density	0.857 g/cm ³ (@ 20°C).	1.419 g/cm ³ (@ 20°C).
Flash point active product	>200 °C (odprta posoda)	>200 °C (odprta posoda)
Density active product	1,419 g/cm ³ (@ 20°C).	1,419 g/cm ³ (@ 20°C).
Operating temperature active product	-40 -->+1400 °C	-40-->+1400 °C
4-ball weld load active product	3800 N	3800 N
NLGI class	3	3

6. Packaging

Aerosol	12x300 ML	Ref. : 10723
	12x500 ML	Ref. : 30108
Razsuto stanje	1 KG	Ref. : 20706
TI	can 12x500 G	Ref. : 32344
TU	12x100 G	Ref. : 10720

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that





Technical data sheet
Metal Free Paste

Reference : 10434

you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-METAL_FREE_PASTE-20131003

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

