

MINUS 50

Reference : 10567



1. General description

Быстро выявляет тепловые дефекты электронного и электротехнического оборудования. Защищает термочувствительные компоненты оборудования во время пайки. Упрощает прецизионную подгонку металлических деталей. Не оставляет налета.



2. Features

- Protects heat sensitive components during soldering and desoldering.
- Facilitates precision fitting of metal parts.
- For testing thermostats and all systems responding to temperature changes.
- Does not leave a residue.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.

3. Applications

- Testing of thermometers and thermostats.
- Locating defective electrical parts.
- Shrink fitting
- Trimming / machining of rubber bushes.
- Electro-mechanical assemblies.
- Control assemblies.
- Electronic components.

**MINUS 50**

Reference : 10567

- Printed circuit boards.

4. Directions

- Use extension tube for more precise application.
- Do not use on energized equipment.
- Do not use on sensitive electronic equipment.
- Spray from a short distance.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Appearance	liquified gas
Color	бесцветный
Odour	Ощутимый запах
Density	1.139 g/cm ³ (@ 20°C)
Vapor density	>3

6. Packaging

Аэрозоль	12x200 ML
	12x500 ML

7. Remarks

The product is a blend of compressed liquid gases, functioning simultaneously as propellant and active product. By condensation of air humidity, frosting up and occurrence of liquid water is possible in the application area.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-MINUS_50-20090626
Date 26/06/2009



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

