

ROST FLASH

Reference : 10526



1. General description

Разрушает структуру ржавчины путем «термического шока». При распылении средства на поверхности происходит резкое охлаждение до -40°C и образуются мелкие трещины, что разрушает коррозионный слой. Масло легко проникает через трещины, обеспечивая освобождение соединений. CRC Rost Flash работает на всех типах поверхностей и деталей, когда разъединение затруднено коррозией. Не содержит силикон или кислоты.



2. Features

- Cracks the layer of rust and dirt using thermal shock (reduces temperature to -40°C).
- Loosens metal parts seized by dirt, corrosion or dried-up grease.
- Penetrates quickly.
- Does not contain silicones.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.

3. Applications

- Cleaning mechanical parts.
- Handling equipment.
- Seized and corroded parts.



ROST FLASH

Reference : 10526

- Agricultural equipment.
- General disassembly.

4. Directions

- Remove most of the loose dirt with a wire brush.
- Spray liberally and allow to run off.
- Use extension tube for more precise application.
- Spray from a short distance.
- Allow a few minutes for good penetration.
- Repeat if necessary.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Appearance	Жидкость
Color	янтарный
Odour	Характерный запах
Density	0.75 g/cm ³ (@ 20°C)
Flash Point	< 0 °C

6. Packaging

Аэрозоль 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-ROST_FLASH_IND-20090619
Date 19/06/2009



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

