



1. General description

Высокоэффективная СОЖ для всех металлов. Благодаря своим исключительным противозадирным свойствам СОЖ особенно подходит для механически труднообрабатываемых металлов и высокопрочных сплавов стали. Увеличивает срок службы инструмента.



2. Features

- Balanced lubrication and excellent cooling reduces friction and provides an increased tool life.
- Lowers operating temperatures and allows for higher operating speeds.
- Stable foam formulation.
- Safe on all metal surfaces, does not stain.
- Баллон оборудован 360° клапаном (работает в любом положении баллона) для удобства пользования.

3. Applications

- Standard cutting operations.
- Standard metals and alloys for machining.

4. Directions

- Shake well before use.
- Распыляйте с короткого расстояния.
- Repeat frequently during the application.
- To remove residues or excess product, use one of the CRC cleaners.
- Листы безопасности (MSDS) согласно Ст.31 Положения ЕС N° 1907/2006 Ст.3 со всеми приложениями



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





доступны для всех продуктов CRC.

• **NOTE:** The product can also be used to upgrade simple cutting oils (use 5% or more), but compatibility and performance should be checked for each case.

5. Typical product data (without propellant)

Внешний вид	Аэрозоль пена.	Большого объема Жидкость.
Цвет	янтарный.	янтарный.
Запах	Характерный запах.	Характерный запах.
Плотность	0.879 g/cm ³ (@ 20°C).	0.879 g/cm ³ (@ 20°C).
Вязкость	55.9 mPa.s (@ 20°C).	55.9 mPa.s (@ 20°C).
Кинематическая вязкость	23.09 mPa.s (@ 40°C).	23.09 mPa.s (@ 40°C).
Flash point active product	>170 °C	>170 °C
4-ball weld load active product	4800 N	4800 N
4-ball wear active product	0.18 mm	0.18 mm

6. Packaging

Аэрозоль	12x300 ML	Ref. : 20448
Большого объема	20 L	Ref. : 30354
	2x5 L	Ref. : 20457
	6x1 L	Ref. : 30353

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Версия CRC_GREEN-SUPERCUT_II-20150304

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

