

1. General description

Растворяет резину, смолы, нагар, клеевые и углеродистые отложения.



2. Features

- Quickly dissolves carburettor deposits, providing faster starting and smooth idling.
- Dissolves soot, gum, carbon and oil deposits.
- None chlorinated solvents.
- Баллон оборудован 360° клапаном (работает в любом положении баллона) для удобства пользования.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Carburettor components.
- Positive Crankcase Venting (PCV) systems and valves.
- Exhaust Gas Recycling (EGR) valves.
- Throttle valve.

4. Directions

- Dismount and wet the contaminated surfaces and allow to act for 5 min. Repeat if needed. Allow the EGR and PCV valve to dry before re-assembling. Start engine at idle. Spray the throttle valve again and accelerate the engine with a couple of short impulses to 2000 rpm.



Technical data sheet Carb & EGR Cleaner

Reference : 10165

- **Carburettor cleaning:**
 - Stop engine and let it cool down. Remove air filter.
 - Spray sparingly into carburettor, wetting all visible parts.
 - Spray exterior surfaces until they are clean and allow to dry.
 - Start engine. Whilst running at medium idle, spray directly into air intake. Accelerate.
 - Stop engine. Lubricate and protect exterior parts and linkages with CRC 5-56.
 - Put filter back into place and, if necessary, adjust air-fuel ratio
- Листы безопасности (MSDS) согласно Ст.31 Положения ЕС N° 1907/2006 Ст.3 со всеми приложениями доступны для всех продуктов CRC.

5. Typical product data (without propellant)

Внешний вид	Аэрозоль	Большого объема
Цвет	Жидкость.	Жидкость.
Запах	бесцветный.	бесцветный.
Плотность	Ароматическое соединение.	Ароматическое соединение.
Точка вспышки	0.832 g/cm ³ (@ 20°C).	0.832 g/cm ³ (@ 20°C).
Температура самовозгорания	< 0 °C (закрытый тигель)	< 0 °C
Плотность испарений	> 200 °C	> 200 °C
Вязкость	3.3 (@ 20°C).	3.3 (@ 20°C).
Kauri Butanol value active product	0.65 mPa.s (@ 20°C).	0.65 mPa.s (@ 20°C).
	> 15000	> 15000

6. Packaging

Аэрозоль	12x300 ML	Ref. : 30491
	6x300 ML	Ref. : 30491

7. Remarks

- If spilled or sprayed on painted surfaces, rubber or sensitive plastics, wipe or wash off immediately.
- Always follow the recommendations in the instruction manual provided by the equipment manufacturer.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





Technical data sheet
Carb & EGR Cleaner

Reference : 10165

this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Версия CRC_RED-CARBURETTOR_CLEANER-20140522

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

3/1

