

## 1. General description



## 2. Features

- Mhux disponibbli.

## 3. Applications

- Mhux disponibbli.

## 4. Directions

- Mhux disponibbli.

## 5. Typical product data (without propellant)

Mhux disponibbli.

## 6. Packaging

ajrusol	12x300 ML	Ref. : 10693
TI	can 12x500 G	Ref. : 10699
TU	12x100 ML	Ref. : 10690
	6x100 ML	Ref. : 10690



## 7. Remarks

Grease decomposition temperature is 300°C. Anti seize properties of the copper particles are conserved up to approximately 1000°C

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC\_RED-COPPER\_PASTE-20160310

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

