



## 1. General description



## 2. Features

- Forms a colourless, non-hardening film, eliminating squeaking, binding and sticking.
- Protects metals and alloys.
- Penetrates quickly.
- Protects plastics and rubbers.
- Displaces and seals out water and moisture.
- Functional over a wide temperature range.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

## 3. Applications

- Plastic drives and sliding mechanisms.
- Precision instruments.



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





- Anti-freeze for rubbers.
- Assembly of packings.
- Protection and maintenance of rubbers.

#### 4. Directions

- Apply a thin even film.
- Use extension tube for more precise application.
- Repeat if necessary.
- Do not use on energized equipment.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

#### 5. Typical product data (without propellant)

Appearance	Aerosol	Razsuto stanje
Barva	Tekočina.	Tekočina.
Vonj	Brez barve.	Brez barve.
Density	Topilo.	Topilo.
Flash Point	0.72 g/cm <sup>3</sup> (@ 20°C).	0.72 g/cm <sup>3</sup> (@ 20°C).
Temperatura samodejnega vžiga	- 26 °C (zaprta posoda)	- 26 °C (zaprta posoda)
Gostota hlapov	> 200 °C	> 200 °C
Flash point active product	>3 (@ 20°C).	>3 (@ 20°C).
Operating temperature active product	>300 °C (zaprta posoda)	> 300 °C (zaprta posoda)
Dynamic viscosity active product	-40 till 200 °C	-40 --> 200 °C
Dielectric strenght active product	10.000 - 12.000 mPa.s (@ 20°C).	10.000 - 12.000 mPa.s (@ 20°C).
Surface tension active product	35 kV	35 kV
	21 mN/m	21 mN/m

#### 6. Packaging

Aerosol	12x200 ML	Ref. : 10506
	12x300 ML	Ref. : 30315
	12x400 ML	Ref. : 10517
	6x200 ML	Ref. : 10506





Technical data sheet  
**Silicone Spray**

Reference : 10275

Razsuto stanje

20 L  
2x5 L

Ref. : 10523

Ref. : 10522

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC\_RED-SILICONE-20131003

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)



3/1