

1. General description

Excellent insulating and sealing rubber silicone compound. Helps to prevent corrosion and arcing.



2. Features

- Excellent water resistance.
- Functional over a wide temperature range.
- Cures at room temperature.
- For all types of surfaces.
- Non conductive.
- Exhibits adhesion to most non-porous substrates, particularly plastics, without the use of a primer.
- Excellent sealing properties.

3. Applications

- Prevents arcing on EHT connections.
- For sealing LNB's in satellite TV installations.
- Electro-mechanical assemblies.

4. Directions

- Apply to a clean, dry surface.
- Do not use on energized equipment.



Technical data sheet SILICONE SEALANT

Reference :

- Allow to dry at room temperature.
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5. Typical product data (without propellant)

Appearance	Paste.
Color	Coloured.
Odor	Characteristic odor.
Density	1.03 g/cm ³ .
Operating temperature active product	-50 to +230 °C
Dielectric strenght active product	17 kV

6. Packaging

TU 24x75 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version KOC-SILICONE_SEALANT-20120522

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com



2/1