



Lubricants



360° Spray System for all angle use

AMBERGLIDE

PTFE LUBRICANT

Amberglide is a multi-purpose, high grade lubricant with PTFE for long lasting lubrication and protection on moving parts in electronic equipment and all areas requiring higher temperature tolerant, longer lasting lubrication.

PRODUCT CODES / FILL SIZES



31571 / 400ml

APPLICATIONS

Especially effective as a high-temperature lubricant on fuser units in photocopiers, where temperatures can reach 150 - 160°C. Also suitable for mechanisms such as:

- Locks
- Hinges
- Tracks
- Clutches
- Chains
- Gears
- Precision Tooling

DIRECTIONS

- Amberglide will clean away surface contamination, displace moisture, prevent squeaking and leave a durable, protective film on the treated part.
- Ensure electrical equipment is switched off before applying Amberglide.
- Apply directly onto the components to be treated.
- After spraying, always leave for at least 4/5 minutes to allow dispersal of solvent vapours, before operating the equipment.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Amber liquid
Odour	Butyl Acetate
SG @ 25°C	0.875
Pressure @ 25°C	3.5
Discharge rate	1.1g /sec
Temperature range	Operational from -10°C to +180°C
Solubility	Soluble in most solvents, insoluble in water
Recommended solvents	Amberklene FE10, ME20, LO30 or Ambertron
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0
Created: July 2019
Updated: N/A

CRC Industries UK Ltd.
Wylde Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

