



Lubricants

## CHAINSPRAY

### CHAIN AND DRIVE LUBRICANT

ChainSpray is a lubricating and protective agent based on a mixture of oils, rust inhibitors and surfactants. It has been formulated to offer maximum adhesion to chain links for protection against rust, whilst also giving full penetration to lubricate the links.

Ensures minimal chain wear and resists throw-off, water wash and dust absorption. Safe to use on running chains and can be applied through inspection holes and guards.

Also available as an alternative product specifically for use on fork lift trucks: FLT ChainSpray.

### PRODUCT CODES / FILL SIZES

 1031013	 1031049
31575 / 400ml	31614 / 500ml (FLT version)

### APPLICATIONS

Suitable for use in many different industries and areas:

- Fork lift trucks
- Bottle washing plant
- Lifting
- Textile machinery
- Canning machinery
- Packaging machinery
- Escalator manufacturers
- Cement and quarry plant chains on furnace doors
- Paper making machinery
- Chain driven belts and machinery

### DIRECTIONS

- Apply an even coating from 9" - 12" (25 - 30 cm) directly onto the part to be treated.
- Re-apply as necessary. In particularly arduous atmospheres (e.g. external applications), the lubricant should be applied frequently.



#### CRC INDUSTRIES UK LTD

Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
e sales.uk@crcind.com  
w www.ambersil.com

Version 4.1  
Created: July 2019  
Updated: April 2025

Company Registered No. 04910479 VAT No. GB 821 5195 42

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Brown foaming lubricant
Odour	Solvent
Specifications/Approvals	MOD Approval to Ref. D/DQA/TS/CS/217/1. Also approved for use by Lansing Bagnall Forklifts
SG @ 25°C	0.72
Pressure @ 25°C	3 Bar
Discharge rate	1.2 g/sec
Temperature resistance	Up to 200°C continuously. Between 200°C and 300°C intermittently, subject to tests on intended application prior to general use
Solubility	Insoluble in water
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

## MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.



### CRC INDUSTRIES UK LTD

Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom  
t +44 (0)1278 727200  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)