



Lubricants

GRAPHITE LOCK LUBE

DRY LUBRICANT FOR SMOOTH, RELIABLE LOCK LUBRICATION

Graphite Lock Lube is a dry graphite lubricant for long lasting, smooth lock operation. The microscopic grains of graphite ensure good penetration and effective anti-seize lubrication. Graphite Lock Lube extends lock life, even in mildly corrosive environments.

The dry film does not attract dirt and grime. Graphite Lock Lube has excellent water resistance, and it works even when lock has mild corrosion. Ideal for corrosive or saline conditions.

PRODUCT CODES / FILL SIZES



33000 / 15ml

APPLICATIONS

- Safety padlocks
- Door locks
- Brass and stainless steel locks
- Padlocks exposed to the weather
- Hinges

DIRECTIONS

- Shake well before use.
- Align nozzle with lock mechanism and spray briefly into key opening.
- Wipe excess off with a clean cloth.
- Repeat if necessary.

TECHNICAL DATA (WITHOUT PROPELLANT)

| | |
|-------------|---------------------------------|
| Appearance | dark grey powder |
| Density | 0.75 g/cm ³ (@ 20°C) |
| Flash Point | <0°C |

MATERIALS COMPATIBILITY

| | |
|---------|---|
| OK | - |
| CAUTION | - |
| NOT OK | - |

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 2 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0
Created: July 2019
Updated: N/A

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

