



Cleaners



Automotive Approval



Aerospace Approval

## AMBERKLENE LO30

### LOWER ODOUR SOLVENT DEGREASER

Amberklene LO30 is a powerful, low odour solvent which contains no CFCs or other chlorinated solvents and is not affected by the Montreal Protocol. It is an ideal alternative to 1,1,1 Trichloroethane.

Can be used for general light degreasing on bearings, motors, gears and chains without the traditional odour associated with solvent degreasers. Will not stress-crack acrylic.

Amberklene LO30 is listed in British Airways 'Standard Practice' manual. Meets US Federal Spec. TT-N-95Bv Type 2; and is approved by Ford Motor Company (Tox: 166741).

### PRODUCT CODES / FILL SIZES



31555 / 400ml



31699 / 5Ltr



31700 / 25Ltr



31701 / 200Ltr

### APPLICATIONS

A highly effective low odour, degreasing agent widely used in aviation and aerospace servicing applications, where its excellent material compatibility, particularly on plastics is a distinct advantage over other solvent cleaners.

For use in numerous industries including:

- Aviation and Aerospace
- PCBs and Electronics
- Optical Devices
- Automotive
- Precision Equipment
- Printing
- Agriculture
- Light and Heavy Engineering
- Moulding
- Offshore
- Marine

Efficiently cleans plastics, ferrous and non-ferrous metals, evaporating to leave a clean, dry surface.

### DIRECTIONS

- Ensure electrical equipment is switched off before cleaning.

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, colourless liquid
Odour	Aliphatic hydrocarbon
Specification/Approvals	Meets US Federal Specification TT- N-95B Type II Listed in British Airways Standard Practice Manual
SG @ 25°C	0.73
Pressure @ 25°C	2 Bar
Discharge rate	3.1 g/sec
Kb value	35
Initial boiling point	100°C
Freezing point	-20°C
Evaporation rate	3.2 (with respect to Butyl Acetate)
Flammability	Classified as extremely flammable under Current EC Regulations
Flashpoint	Not applicable in sealed aerosol

## MATERIALS COMPATIBILITY

OK	Safe for use on ferrous and non-ferrous metals, most painted surfaces, and most plastics
CAUTION	May affect certain delicate plastics. Always test a small, inconspicuous area before use.
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0  
Created: July 2019  
Updated: N/A

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

