



## MACHINE OIL FG

### FOOD PROCESSING SAFE® GENERAL PURPOSE LUBRICANT

Machine Oil FG is a general purpose lubricant and penetrating oil. An extremely efficient and effective general purpose lubricant for use on food processing equipment where incidental food contact may occur. Based on pharmaceutical grade highly refined white oils. Machine Oil FG exhibits excellent penetrating ability and loosens rust, scale, dirt and corrosion to free parts and fasteners.

Creates an effective water-repellent film, that prevents corrosion and lubricates efficiently over a wide temperature range. Contains no silicone.



Lubricants



360° Spray System for all angle use



NSF Registered: category H1, no. 137999 (400ml) & 140249 (5 ltr)



Just one of over 25 FG products



Prevention. Not Detection. Locked in for safety

### PRODUCT CODES / FILL SIZES



30247 / 400ml



30255 / 5Ltr

### APPLICATIONS

- Bakery equipment
- Meat + poultry processing + packing equipment
- Bottle filling machinery
- Stainless steel pumps
- Filters
- Chain drive belts
- Valves
- General wipe down lubricant
- Pistons
- General lubrication during equipment installation
- Rollers

### DIRECTIONS

- Apply a light, even film
- Allow a short time for penetration before use
- Wipe off excess with cloth
- Repeat application when necessary
- If necessary, non-drying film can be removed by Ambersil Amberklene FG
- Do not use on energised (live) equipment

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, Colourless Liquid
Specific Gravity (@ 20°C)	0.82
Flash Point (closed cup)	74°C
Vapour Density (solvent, air = 1)	6
Colour Saybolt	+30
Kinematic Viscosity (@ 20°C)	83 mPa.s
Kinematic Viscosity (@ 40°C)	26 mPa.s
Flash Point (open cup)	175°C
Pour Point	-18°C
Temperature Range	-18°C to +120°C (150°C short time)
Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives	

## MATERIALS COMPATIBILITY

OK	Safe for use on metals, most plastics, painted surfaces and wood. If in doubt, on-the-job testing prior to use is advised
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0  
Created: July 2019  
Updated: N/A

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

