



Paints








## MARKER PEN

### FAST DRYING, MULTI-SURFACE, MARKER PENS

Marker Pens can be used exactly like regular ink permanent markers, but without the drawbacks typically associated with them. The acrylic paint is highly tenacious, able to write on almost any surface, and on any substrate colour. The very high opacity ensures outstanding colour vibrancy and visibility, and the advanced pigment technology delivers very long lasting, zero fade performance. Tenacious resin binds paint to the writing surface almost eliminating the problems associated with accidental rub-off and will not wash off with water/rain.

Marker Pens have durable tip with valve action to prevent excess paint flow, with easy accurate application (medium thickness point Ø 3 mm).

### PRODUCT CODES / FILL SIZES

COLOUR	CODE	COLOUR	CODE
 WHITE	20394	 RED	20387
 GREEN	20379	 ORANGE	20383
 YELLOW	20399	 BLACK	20364
 BLUE	20368		



3mm / Colour squares are representative only

### APPLICATIONS

Most industrial marking requirements

- Metal working/fabrication
- Electrical installations
- Machine construction
- Civil engineering
- Road construction
- Logistics
- Surveying
- General repair

### DIRECTIONS

- Shake the pen well with the cap on, until the agitator ball moves freely.
- Take off the cap and press the tip several times or until the paint starts to flow.
- Always use in a well ventilated area.
- Replace the cap carefully after use and store in horizontal position.
- The colour may fade when exposed to direct sunlight for an extended period.
- The marker pens can be removed easily with a solvent such as Amberklene FE10.

## TECHNICAL DATA (WITHOUT PROPELLANT)

Colour	7 colours available: Yellow, White, Blue, Black, Orange, Red, Green
Flash Point	25°C
Specific Gravity	0.9
Boiling Point	> 100°C

## MATERIALS COMPATIBILITY

OK	Metal, rubber, glass, textile, paper, enamel, plastic, cardboard, tiles, wood
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 4 years with correct storage.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0  
Created: July 2019  
Updated: N/A

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

