

## Technical Data

### **QS 900** **QUICK STICK ADHESIVE**



**SPRAY ADHESIVE QS 900** is a fast tacking, non-chlorinated spray adhesive. This specialist formulation will provide instant 'grab', which allows pressure to be exerted on the bond before full cure strength is achieved.

#### ADVANTAGES

- Quick stick - provides instant grab
- Provides permanent bonds
- Free from chlorinated solvents
- Tack time approximately 30 seconds
- Economical in use - only a light film is required for instant grab

#### APPLICATIONS

QS 900 Quick Stick Adhesive has been formulated to satisfy the demands of the carpeting and flooring trade. It is also suitable for bonding many different substrates, including:-

- Carpet
- Underlay
- Foam
- Fabric
- Cork
- Upholstery
- Paper, Cardboard
- Wood

To a wide variety of different surfaces.

Apply a light, fine even coating to both surfaces to be bonded from 9" - 12" (25 - 30 cm). Wait until the adhesive is tack-dry and bond the surfaces together using firm pressure. **Heavier applications of QS 900 may prolong the tack time. N.B. May affect certain plastics. Always test a small, inconspicuous area before general use. To prevent blockages, invert the can after use and spray to clear the nozzle.**

#### TECHNICAL DATA

Appearance	:	Clear, amber liquid
Odour	:	Characteristic Solvent
SG @ 25°C	:	0.66
Pressure @ 25°C	:	4 Bar
Discharge rate	:	1.2 g/sec
Polymer type	:	Styrene Butadiene Rubber
Tack time	:	Approximately 30 seconds

Bonding time	:	Maximum adhesion in 12/24 hours
Temperature range	:	Up to 50°C (dried film)
Solubility	:	Soluble in some solvents, insoluble in water
Recommended solvents	:	Amberklene FE10, ME20
Flammability	:	Classified as extremely flammable under CHIP Regulations
Packaging	:	500ml aerosol (12 per carton)

### **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

### **TECHNICAL SERVICE**

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

### **MISREPRESENTATION ACT 1967      TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylde Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: [www.ambersil.com](http://www.ambersil.com)

E-mail: [sales.uk@crcind.com](mailto:sales.uk@crcind.com)