



CRC CARBURETTOR CLEANER

Ref. : 10165

1. GENERAL DESCRIPTION

Heavy duty carburettor parts cleaner.

A fast acting solvent formulation which combines the high solvency action of aromatic and polar solvents.

Carburettor Cleaner is designed to restore carburettor performance without disassembling and helps to maintain the system clean.

2. FEATURES

- Quickly dissolves carburettor deposits.
- Removes gum, varnish, lacquers, resin, paraffin, tar and gasoline stains.
- Gives faster starting and smooth idling.
- Ensures maximum fuel economy.
- Will not harm catalytic converters and oxygen sensors.
- Reduces hydrocarbon emissions and controls pollution of cars without a catalytic converter.
- Saves maintenance time.
- Eliminates the need of wire brushes, thus avoiding damage to soft metal alloys.
- Free of chlorinated solvents.
- Aerosol is equipped with a 360° (upside-down) spray valve and extension tube for added convenience and pinpoint application.
- Aerosol is pressurized with CO₂ propellant, giving an active product content of over 97%.

3. APPLICATIONS

- Carburettor components
- Automatic chokes
- Positive Crankcase Ventilating (PCV) systems and valves
- Crankcase breather elements
- Exhaust gas recycling valves (EGR)
- Heat control valves
- Fuel systems

4. DIRECTIONS

4.1 Carburettor cleaning

- Stop engine and let it cool down. Remove air filter.
- Spray sparingly into carburettor, wetting all visible parts.
- Spray exterior surfaces until they are clean and let dry.
- Start engine. Whilst running at medium idle, spray directly into air intake. Accelerate.
- Stop engine. Lubricate and protect exterior parts and linkages with CRC 5-56.
- Put filter back into place and, if necessary, adjust air-fuel ratio.



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC CARBURETTOR CLEANER

Ref. : 10165

4.2 Other cleaning applications

- Make parts to be cleaned accessible by removing covers, disconnecting hoses, etc.
- If possible, spray from all sides, let penetrate and move back and forth. Clean heat control valves, automatic chokes, EGR valve with ignition off and engine cool. Clean PCV system with engine running at fast idle.
- Re-lubricate with CRC 5-56 where necessary and replace covers, hoses, etc.

Notes:

- If spilled or sprayed on painted surfaces, rubber or sensitive plastics wipe or wash off immediately.
- Always follow the recommendations in the instruction manual of the equipment manufacturer.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	:	colorless liquid
Odor	:	aromatic
Specific gravity @ 20°C	:	0,85
Boiling range	:	60-160°C
Vapor density (vs. air = 1)	:	3,3
Freezing point	:	< -30°C
Evaporation rate (vs. ether = 1)	:	7
Flash point (closed cup)	:	< 0°C
Viscosity @ 20°C	:	0,65 mPa.s
Kauri-Butanol value	:	> 15000

6. PACKAGING

Aerosol: 12 x 300 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10165 03 0197 02
Date : 23 september 2003



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

