



## CRC OIL ADDITIVE

Ref. : 10300

### 1. GENERAL DESCRIPTION

---

CRC Oil Additive is a multipurpose additive for crankcase oils combining advanced organo-metallic compounds in a high-purity paraffinic oil.

Ideally suited for stop-go driving, caravan and trailer touring and other difficult engine operating conditions.

### 2. FEATURES

---

- Assures consistent, reliable engine operations.
- Improves peak efficiency and performance.
- Decreases sludge and varnish formation and piston deposits.
- Reduces internal friction and engine wear.
- Prevents untimely oxidation and ageing of the oil.
- Provides excellent rust and corrosion inhibition to the entire oil system.
- Keeps the engine cleaner, quieter and smoother-running.
- Contributes to extended oil life and longer service intervals.
- Contributes to a better combustion and fuel economy.
- Compatible with all commonly used oils, including synthetic and "turbo"-types.

### 3. APPLICATIONS

---

- Motor bikes
- Cars
- Trucks
- Busses
- Boats
- Farm and garden equipment
- Stationary combustion engines

### 4. DIRECTIONS

---

- Add CRC Oil Additive to engine oil every 5.000 km. Make sure not to go over max. oil level. Check miscibility with synthetic lubricants.
- Compatible with P.A.O. based synthetic lubricants and all mineral oils.
- 1 can treats up to 5 L of engine oil.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





## CRC OIL ADDITIVE

Ref. : 10300

### 5. TYPICAL PRODUCT DATA (without propellant)

---

Appearance	:	brown viscous liquid
Specific gravity @ 20°C	:	0.92
Viscosity @ 40°C	:	400 mPa.s
Pour point	:	-15 °C
Flash point (open cup)	:	>180 °C
CCMC elastomer compatibility test (5x recommended CRC dose)		
Viton	:	pass
Acrylate	:	pass
Silicone	:	pass
Nitrile	:	pass

### 6. PACKAGING

---

bottle : 12 x 250 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com). We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10300 03 0198 01  
Date : 23 september 2003



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

