



1. GENERAL DESCRIPTION

High quality primer for untreated surfaces made out of metal, wood, ceramic, glass and a variety of plastics.

2. FEATURES

- Fast drying
- Good filling ability
- Excellent hiding power, giving an excellent surface preparation for lacquering.
- Can be lacquered with alkyd, nitro-cellulose, 1K & 2K acrylic paints
- High corrosion protection for metals
- Can be sanded wet or dry with sanding paper as from grain 400 and up

3. APPLICATIONS

Pre treatment, before lacquering, of

- Metal rims
- Wood
- Plastics
- Ceramics
- glass

On the car, at home and for leisure equipment.

4. DIRECTIONS

- Remove old paint and scale and corrosion before application.
- Make sure the surface is well sanded, clean and dry.
- Assure the aerosol is at room temperature and shake for 2 minutes.
- Make a test on a separate or hidden part.
- Apply the primer in thin even cross layers from a distance of 25 to 30 cm.
- Shake the aerosol between each layer
- Clean the valve after use, by spraying upside down until only gas escapes.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.





CRC PRO PAINT
Primer

Ref. : 10630

5. TYPICAL PRODUCT DATA (without propellant)

Resin type	:	nitro-cellulose binder
Temperature resistance	:	110°C
Covering	:	1,5 to 2 m ² / 500 ml
Drying times (*)	to dust	: 5 – 10 minutes
	Stick free	: 10 – 20 minutes
	Cured / over paintable	: 2 hours

() depending on coat weight, ventilation, temperature and relative humidity*

6. PACKAGING

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10630 03 1105 00
Date : 22 November 2005



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

