



## CRC DIESEL ANTI- PARAFFIN

Ref. : 10310

### 1. GENERAL DESCRIPTION

---

Diesel fuel cold flow improver.

A synthetic polymer additive concentrate incorporated in a high flash point active filter cleaning solvent. Diesel Anti-Paraffin improves diesel fuel cold flow characteristics by modifying the crystal structure of paraffin's (waxes) and lowering the "cold filter plugging point" (CFPP) and the pour point.

### 2. FEATURES

---

- Hinders wax crystal growth.
- Improves diesel fuel low temperature fluidity.
- Keeps fuel flowing through the filter.
- Prevents cold starting and driving problems.
- Prevents downtime.
- Much safer than blending diesel fuel with kerosene or gasoline.
- Does not lower the fuel's flash point.
- No reduction of self-lubricating properties.
- Most economical way to improve diesel fuel's cold flow properties.

### 3. APPLICATIONS

---

- Cars
- Busses
- Trucks
- Tractors
- Storage tanks of diesel and heating fuel

### 4. DIRECTIONS

---

- Shake before use.
- Add CRC Diesel Anti-Paraffin to fuel **before** the first crystals appear, i.e. before low temperature conditions (< 0°C) occur.
- Pour CRC Diesel Anti-Paraffin into fuel tank **before** filling up to obtain complete mixing.

When using the 150 ml packing:

- 150 ml treats 50 l fuel.

When using the 1 liter packing:

- 1 liter treats 2000 liter fuel in bulk storage tanks.
- During extreme weather conditions, higher doses may be needed, up to 1 liter on 500 liter fuel.

- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
www.crcind.com





## CRC DIESEL ANTI- PARAFFIN

Ref. : 10310

### 5. TYPICAL PRODUCT DATA

---

Appearance	:	colorless
Odor	:	aromatic
Specific gravity @ 20°C	:	0,90
Flash point	:	62°C

### 6. PACKAGING

---

Bottle:	12 x 150 ml
Cannister	6 x 1 liter
Cannister	4 x 5 liter

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10310 03 0197 05  
Date : 09 January 2006



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

