



CRC MULTILUBE

Ref. : 10703

1. GENERAL DESCRIPTION

Water resistant, multipurpose lubricant.

A specially formulated blend of high quality mineral and synthetic oils, with anti-wear additives, friction modifiers and tackiness agents. Multilube Transparent does not drip off, penetrates deeply into vital hinges and bushing areas, and then sets to form a water resistant, long lasting lubricant film. Designed even for highly loaded reciprocal moving parts, high power and shock load conditions.

2. FEATURES

- Resists hot and cold water wash-off.
- Resists high temperature friction points.
- Reduces friction and wear.
- Reduces noise and vibration.
- Reduces the resistance when tightening screws and bolts (especially stainless steel).
- Extends chain life.
- Compatible with o-rings mounted in chains.
- Harmless to metals and most plastics and rubbers (test before using on plastic or rubber parts).
- Does not contain chlorinated solvents.
- Aerosol formula uses hydrocarbon propellant and is provided with a small-angle nozzle and an extension tube for precise, controlled application and film thickness.

3. APPLICATIONS

- Hinges.
- Door stops on cars.
- Articulation points.
- Valve stems.
- Sliding rails for venting roofs, sliding doors, car & truck seats.
- Hoists.
- Conveyors (also overhead conveyors).
- Coupling mechanisms.
- Forklifts.
- Overhead door drives.
- Tractors and farm equipment.
- Car wash equipment.
- Window mechanisms.
- Threaded connections (especially stainless steel).
- Friction bearings.
- Spindles (caravans & small trailers).



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC MULTILUBE

Ref. : 10703

4. DIRECTIONS

- Do not mix with other lubricants. Clean parts to be lubricated with CRC Quickleen and let dry.
- Apply evenly onto the friction point and allow product to penetrate and set for a few minutes.
- Move the friction points during the penetration phase
- Excess or spilled product can be removed with CRC Quickleen.
- Do not use on equipment under electrical tension.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	:	transparent, fresh blue
Specific gravity @ 20°C	:	0,80
Flash point (solvent, closed cup)	:	< 0 °C
Dry film properties		
Specific gravity @ 20°C	:	0.87
Kinematic viscosity @ 40°C	:	1795 - 1995 mm ² /s.
Flash point (open cup)	:	230°C
Brugger wear test	:	65N/mm ²
Four ball wear ASTM D2266 solids mm ²	:	0,25
Operating temperature	:	-35°C till 200°

6. PACKAGING

Aerosol: 12 x 500 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10703 03 0602 04

Date : 09 February 2004



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

