



TECHNICAL DATA  
1/2

**CRC BELT GRIP**  
**Stops slipping.**  
Ref. : 20137



### 1. GENERAL DESCRIPTION

---

Adhesive belt lubricant. Water resistant. Aids transmission efficiency and gives extra pulling power. Stops slipping and squeaking.

### 2. FEATURES

---

- Prevents slippage on flat, round and V-belts.
- Adheres strongly to any belt material.
- Gives extra pulling power, enhances transmission efficiency.
- Reduces squeaking noise caused by belt slipping.
- Forms a tacky, non-drying, water-resistant, chemically stable film.
- Compatible with all commonly used types of belt materials (rubber, leather, fabrics, ...).
- NSF registration:H1 (registration number: 139822).

### 3. APPLICATIONS

---

Eliminates slippage in flat, round or V-belts made out of rubber, leather, fabrics, plastic,... used in:

- Compressors
- Pumps
- Generators
- Fans
- Motors
- Conveyors
- Industrial machinery

### 4. DIRECTIONS


---

- Turn off equipment and stop belts before applying.
- Spray a light, even coating on the pulling sides of the belt (i.e. sides that come in contact with pulleys); let solvent evaporate before re-energizing equipment.
- Re-apply occasionally to ensure continued high performance.
- Removal, if necessary, by CRC Industrial Degreaser (test compatibility with rubbers and plastics prior to use).



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





TECHNICAL DATA  
2/2

**CRC BELT GRIP**  
**Stops slipping.**

Ref. : 20137

***A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.***

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.

**5. TYPICAL PRODUCT DATA (without propellant)**

---

Appearance	:	clear liquid
Specific gravity (@ 20°C)	:	0,75
Flash point (closed cup)	:	< 0°C
Dry film properties		
Specific gravity (@ 20°C)	:	0,91
Max. temp. (cont.)	:	100°C
Auto ignition temperature	:	> 200°C

**6. PACKAGING**

---

Aerosol : 12 x 400 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 20137 03 0108 02  
Date : 08 December 2015



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

