

TECHNICAL DATA
1/2

CRC FOODKLEEN
Heavy duty cleaner / degreaser
Ref. : 10078



1. GENERAL DESCRIPTION

Heavy duty non-chlorinated solvent cleaner for use on food processing equipment and in inedible product processing areas. Dissolves and removes grease, oil, lubricants, tar, adhesives and other contaminants. Reduced flammability risk due to a flash point of 40°C. Leaves no residue.

2. FEATURES

- High flash point of 40°C for application safety.
- Dissolves grease, oil, lubricants, tar and adhesives.
- Penetrates quickly and removes dirt and humidity.
- Cleans and degreases equipment, metal parts and machinery.
- Neutral product, non-staining.
- Without chlorinated solvents.
- Non-corrosive to metals.
- May be harmful to plastics and will soften some paints.
- Aerosols are equipped with the 360° (upside-down) spray valve for added convenience. High purity CO₂ propellant, giving an active product content of 97%.
- NSF registration A8/C1
 - registration number aerosol: 111200.
 - registration number bulk: 139910.

3. APPLICATIONS

Effective removal of grease, oil, dirt and other contaminants from:


- | | |
|----------------------------------|-------------------------------|
| • Motors | • Generators |
| • Mechanical brakes and clutches | • Sprockets |
| • Dies | • Material handling equipment |
| • Pumps | • Air tools |
| • Chains | • Wire ropes |
| • Moulds | |

A safety data sheet (MSDS) according to EC Regulation N°1907/2006 Art.31 and amendments is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC FOODKLEEN
Heavy duty cleaner / degreaser

Ref. : 10078

4. DIRECTIONS

- Apply liberally and allow excess to run off.
- Air dry or wipe with absorbent cloth.
- Repeat if necessary.
- Check solvent compatibility for your application prior to use. If in doubt, test on a small area.
- Use with adequate ventilation. Do not use on energized equipment. Allow to dry thoroughly and vent before reactivating system.
- After application, re-lubricate moving parts.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: colorless liquid
Specific gravity (@ 20°C)	: 0,78
Flash point (closed cup)	: 40°C
Boiling range	: 140 - 170°C
Evaporation rate (ether = 1)	: 40
Pour point	: < -100°C
pH	: neutral
Solubility in water	: low
Kauri-Butanol value	: > 200

6. PACKAGING

Aerosol : 12 x 500 ml
Bulk : 4 x 5 l

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10078 03 0799 06
Date : 04 February 2010



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

