

TECHNICAL DATA

1/2

CRC ROST FLASH

Ref. : 10526

1. GENERAL DESCRIPTION

Quick acting penetrating oil with freeze effect.

A no compromise product that destroys the structure of rust and corrosion by thermal shock. The created fissures allow a fast penetrating of the oil through the oxides and soil to free corroded fasteners and mechanical components.

2. FEATURES

- Cracks the layer of rust and dirt by means of a big thermal shock (down till -40°C)
- Penetrates quickly into hard-to-reach areas.
- Frees metal parts seized by dirt, rust, corrosion or dried-up greasy deposits.
- Eases quick disassembly of mechanical components, fittings, assemblies, nuts and bolts and other close tolerance fasteners.
- Lowers maintenance costs.
- Reduces scrap rate of seized parts.
- Does not contain silicones.
- Safe for all metals and for most plastics and rubbers (if in doubt, on-the-job testing prior to use is advised).
- Aerosols are equipped with the 360° (upside-down) spray valve and extension tube for added convenience.

3. APPLICATIONS

- | | |
|------------------------------------|--------------------------|
| • Seized and rusted nuts and bolts | • Valves |
| • Locks and hinges | • Air tools |
| • Screwed parts | • Chains and conveyors |
| • Equipment disassembly | • Agricultural equipment |
| • Corroded fasteners | |


4. DIRECTIONS

- Take away most of the loose dirt.
- Apply liberally, from a short distance, saturating problem areas.
- Use extension tube for hard-to-reach areas.
- Allow a few minutes for penetration.
- If necessary, for stubborn joints, fasteners and assemblies, repeat after 2 minutes.
- If wanted, the excess of Rost Flash can be removed with CRC Quickleen.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





TECHNICAL DATA 2/2

CRC ROST FLASH

Ref. : 10526

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: liquid, amber
Odour	: typical
Specific gravity @ 20°C	: 0,75
Flash point (Tag Closed Cup)	: < 0°C
Temperature drop effect	: till – 40°C on the surface
Horizontal spread (after 120 s, @20°C)	: 19 cm ²

6. PACKAGING

aerosol : 12 x 500 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10526 03 0504 01

Date : 12 April 2005



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

