



1. GENERAL DESCRIPTION

Mould release for plastics and rubbers that need ulterior finishing.

2. FEATURES

- Colourless film.
- Temperature operational up to 230°C.

Avoids craterisation of paints at spreading.

3. APPLICATIONS

Moulding of low density polyethylene (sensible to stress cracking).

R 20 is particularly adapted for the moulding of parts still to be painted, (screen)printed, thermo-welded.

- NB : F = flammable

4. DIRECTIONS

1. A safety sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for the products.

5. TYPICAL PRODUCT DATA (without propellant)

Alkyl methyl oil in a solvent base.

Viscosity 3000 cPs.

6. PACKAGING

Aerosol: 12 x 500 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Versie : 20641 03 0903 01

Datum : 12 janvier 2005



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

